

ECON® Hydraulic actuator Series: ESL Type: 21401 Linear Single acting, spring closing

Characteristics

Series: ESL **Type:** 21401

Transmission: Linear Type of drive: Hydraulic

Operating principle: Single acting, spring closing

Signal pressure: 135 bar Test pressure: 240 bar

Top flange standard: Manufacturer standard With mechanical setting indicator: Yes

Hydraulic connection: 1/4" BSP Material housing: Ductile cast iron Material quality: GGG40.3 (GJS-400-15) Housing surface protection: Epoxy coated

Spindle material: Stainless steel Material bolts: Stainless steel Ambient temperature: -20 / 80 °C

Application

- The linear hydraulic actuator is suitable for actuating Larger models available upon request shut-off valves and gear boxes.
- The modular design makes it easy to equip the actuator with a variety of hydraulic accessories.

Technical Information

- Single acting with a force of up to 9100N
- Linear stroke of up to 53mm
- Operating temperature of -20°C to +80°C
- Nodular cast iron housing
- Visual position indicator
- Operating pressure: 135bar

Construction

- Linear design
- Disc springs for spring reset functionality
- Standardised bottom connection
- Can be fitted on a shut-off valve using the assembly
- Hydraulic connection via standardised connecting flange with 0.25-inch BSP female thread
- Non-corroding two-component coating

Execution

• Single acting open/closed

Approval

• Lloyd's Register type approval.

Options

- Additional coating for specific applications
- Equipped with a control box containing reed switches
- Equipped with a powerpack from the EHP-SA series


Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



PR1579278045768563_EN_09.05.2024

Actuators for Valves | Hydraulic actuators





Size table:

Model	Α	D	Н	L	Weight
	mm	mm	mm	mm	kg
ESL-1	109	76	300	162	10
ESL-2	152	116	444	162	40

Type of regulation	Model	Shaft diameter	Article		
	mm				
On/Off	ESL-1	22	14015409		
On/Off	ESL-2	30	14015410		

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.