



GF Butterfly valve Series: 565 Polyamide/PVDF/PA6-60 Bare stem Wafer type

Characteristics

Series: 565
Valve design: Centric
Housing material: Polyamide
Material quality: PA6-60
Connection: Wafer type
Standard connection: EN (DIN)/ ASME
Operation: Bare stem
Disk material: PVDF/PA6-60
Primary spindle seal material: FPM (FKM)

Application

- Water applications.
- Light industry.

Technical Information

- High-quality material.
- Non-corroding.
- Low weight.

Construction

- Wafer-type construction.
- Built-in length in accordance with EN 558 Series 20, ISO 5752 Series 20 and API 609 Table 2.

Approval

- Various seals of quality are available on request.

Options

- Operation with worm gearbox, pneumatic or electric drive.

Nominal inner diameter	External tube diameter of connection	Pressure rating	Pressure rating flange	Face to Face length	Material liner	Article
	mm			mm		
DN50	63	PN16	PN10	43	EPDM	14228539
DN50	63	PN16	PN10	43	FPM (FKM)	14228548
DN65	75	PN16	PN10	46	EPDM	14228540
DN65	75	PN16	PN10	46	FPM (FKM)	14228549
DN80	90	PN16	PN10	46	EPDM	14228541
DN80	90	PN16	PN10	46	FPM (FKM)	14228550
DN100	110	PN16	PN10	52	EPDM	14228542
DN100	110	PN16	PN10	52	FPM (FKM)	14228551
DN125	140	PN16	PN10	56	EPDM	14228543
DN125	140	PN16	PN10	56	FPM (FKM)	14228552
DN150	160	PN16	PN10	56	EPDM	14228544
DN150	160	PN16	PN10	56	FPM (FKM)	14228553
DN200	225	PN10	PN10	60	EPDM	14228545
DN200	225	PN10	PN10	60	FPM (FKM)	14228554
DN250	280	PN10	PN10	68	EPDM	14228546
DN250	280	PN10	PN10	68	FPM (FKM)	14228555
DN300	315	PN6	PN10	78	EPDM	14228547
DN300	315	PN6	PN10	78	FPM (FKM)	14228556

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.