



SKF High load food grade grease LGFQ 2

High load food grade grease

SKF LGFQ 2 is a synthetic oil based grease using the latest complex calcium sulphonate thickener technology. It is suitable for applications subjected to high loads, wet environment and fluctuating temperatures encountered in the food and beverage industry.

Features & benefits

- Excellent corrosion protection
- Excellent mechanical stability
- Excellent high load lubricating capacity
- Good false brinelling protection
- Good pumpability down to low temperatures
- NSF H1 registered and Halal and Kosher certified

Typical applications

- Pellet presses (pet food, sugar, salt)
- Mixers
- Mills
- Centralized lubrication systems

Characteristics

Series: LGFQ 2

Application: Lubrication - grease

Temperature range: -40 / 140 °C

Colour: Brown

Dropping point: > 300 °C

Thickener: Calcium-complex

Base oil type: Synthetic (PAO)

Norm: NLGI 1-2

DIN standard: DIN 51825 KP1/2N-40

Worked penetration 0.1mm: 280-310

Volume l	Content kg	Packaging	Article
	18	Bucket	13413733
0.42		Cartridge	13574602

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.