



LENZING Cartridge filter body Type: 24110 Stainless steel Internal thread (BSPP) 7 bar

Characteristics

Type: 24110

Housing material: Stainless steel

Internal element connection: DOE + Code 3

Connection: Internal thread (BSPP)

With filter element: No

PED classification: PED 2014/68/EU fluid group 2

Application

- Liquids.
- Horizontal pipes.
- Suction and delivery piping.
- Recommended in: Food & Beverages, Food primary processes [contact with food]

Technical Information

- Filter housing made of 304 stainless steel, designed for low pressure differences.
- Suitable for mounting size 10 filter elements.
- Maximum operating pressure 7 bar.
- The 7-bar version is suitable for DOE and Code 3 filter elements [222 O-rings/SOE flat].
- Connections with BSP female thread.
- EPDM seal.

Execution

- Cover can be closed with clamping strip and turnbuckle.
- Polished surface.
- Fitted with drain plug.

Approval

- Suitable for PED 2014/68/EU Art. 4.3 [SEP].

Options

- FPM (FKM), NBR or other seal.
- Filter housing in various sizes

Material quality	Nominal inner diameter	Max. operating pressure bar	Article
SS304	1" [25]	7	14234182
SS304	1" [25]	7	14234184
SS304	1" [25]	7	14234186
SS304	1" [25]	7	14234188

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.