

ADCA Ball float steam trap Type: 5933E Series: FLT steel maximum pressure difference 14 bar flange

ADCA float steam traps are universally applicable in all steam systems. The float mechanism guarantees a direct discharge of condensate at steam temperature. There is no stalling or subcooling in front of the steam trap, enabling a maximum heat transfer to take place in your heat exchanger. Due to the integrated bi-metal vent, the ADCA float steam traps will quickly discharge the air and other non-condensable gases during the start-up, which significantly reduces the start-up time. Due to the modulating action of the float, the ADCA float steam traps are insensitive to sudden changes in capacity or pressure. Another considerable advantage is that you can adjust the flow direction yourself; both from left to right and vice versa, as to vertical.



Characteristics Series: FLT

Type: 5933E Connection: Flange Standard connection: EN 1092-1/02 Maximum pressure difference: 14 bar PMA - maximum allowable pressure: 40 bar TMA - maximum allowable temperature: 300 °C PMO - maximum operating pressure: 32 bar TMO - maximum operating temperature: 250 °C Housing material: Steel Material bonnet: Steel Seat material: Stainless steel 303 (1.4305) With automatic de-aerator: Yes With built-in filter: No Approvals: PED 2014/68/EU fluid group 2

Application

- Universally applicable for directly discharging of large quantities of condensate in among others: Heat exchangers.
- Air heaters.
- Counter current devices.

Technical Information

- CE marking Group 2 (PED European Directive): Version DN15, DN20, DN25 normal capacity: Category SEP.
- Version DN40, DN50 normal capacity: 1 (CE marked).
- Version DN25, DN50 high capacity: 1 (CE marked).

Options


- Steam Lock Release (SLR).
- Vent valve (HVV).
- Drain valve (BDV).
- Anti Freezing Unit (AFZ).
- Float lever (FLL).
- Vacuum breaker (VB21M).


Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/2



Steam Traps | Ball float steam traps





Size	tab	e:
0120		

DN	Capacity	А	В	D	С	E	Weight
		mm	mm	mm	mm	mm	kg/s
DN15	SC	150	160	139	60	79	6.2
DN20	SC	150	160	139	60	79	6.7
DN25	HC	160	212	189	73	116	12
DN25	SC	160	160	139	60	79	7.4

Capacity table in kg/h										
Capacity	DN	Pressure differeSCe (bar)								
		0.5	1	1.5	2	4.5	7	10	12	14
SC	DN15 t/m DN25	220	277	318	365	481	556	654	691	710
HC	DN25	335	445	515	600	885	1150	1350	1500	1610

Connection size	Pressure rating	Capacity type	Material quality body	Material quality	Mounting direction	Flow direction	PED classification	Article
DN15	PN40	SC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Vertical	downward	PED-SEP	14415256
DN15	PN40	SC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Horizontal	$\text{left} \rightarrow \text{right}$	PED-SEP	14415257
DN15	PN40	SC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Horizontal	$\text{right} \rightarrow \text{left}$	PED-SEP	14257618
DN20	PN40	SC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Vertical	downward	PED-SEP	14415258
DN20	PN40	SC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Horizontal	$\text{left} \rightarrow \text{right}$	PED-SEP	14415259
DN20	PN40	SC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Horizontal	$\text{right} \rightarrow \text{left}$	PED-SEP	14257619
DN25	PN40	HC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Vertical	downward	PED cat. I	14415332
DN25	PN40	HC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Horizontal	$\text{left} \rightarrow \text{right}$	PED cat. I	14415333
DN25	PN40	HC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Horizontal	$\text{right} \rightarrow \text{left}$	PED cat. I	14257621
DN25	PN40	SC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Vertical	downward	PED-SEP	14415260
DN25	PN40	SC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Horizontal	$\text{left} \rightarrow \text{right}$	PED-SEP	14415261
DN25	PN40	SC	ASTM A216 WCB/1.0619	ASTM A216 WCB/1.0619	Horizontal	$right \to left$	PED-SEP	14257620
DN25 PN40 SC ASTM A216 ASTM A216 WCB/1.0619 Horizontal right \rightarrow left PED-SEP 14257620 Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.								

ERIKS BV

Tel: +31 88 855 81 84

