

PISTER Ball valve Series: BKH Type: 1950 Steel Internal thread (NPT) PN350 to PN500

Characteristics

Series: BKH

Type: 1950

Norm: ASME

Construction type: 2-way

Housing construction: 3-part

Housing material: Steel

Material quality: Forged steel


Connection: Internal thread (NPT)

Primary spindle seal material: PA (Nylon)

Secondary spindle seal material: NBR

Body seal: NBR

Actuator material: Steel, galvanized



DN ["]	d [mm]	B	H	M	L	Weight [kg]
1/8	5	9	59	107	69	0,35
1/4	6	12	59	107	69	0,35
3/8	10	12	61	107	73	0,5
1/2	13	14	77	107	85	0,65
3/4	20	17	92	165	96	1,5
1	24	19	98	165	113	2
1.1/4	32	20	93	210	110	3,2
1.1/2	38	22	111	210	120	4
2	48	28	127	210	140	5,9

Size	Temperature range	Max. operating pressure	
		Steel	Stainless steel
1/8" - 1/2"	-20°/+90°C	500 bar	400 bar
3/4"	-20°/+90°C	400 bar	350 bar
1"	-20°/+90°C	350 bar	350 bar
1.1/4" - 2"	-20°/+90°C	400 bar	400 bar

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Bore	With locking device	Material ball	Seat material	Spindle material	Article
3/8" [10]	ASME B1.20.1	PN500	Manufacturer standard	Handle	Full bore	No	Steel	PA (Nylon)	Steel	11812740

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.