

SKF Pillow block housing Series: FSAF

SAF split pillow (plummer) block housings are popular SKF bearing housings with inch dimensions. Different housing variants and seal designs are available, making the use of tailored housings virtually unnecessary and enabling cost-effective bearing arrangements. SAF and housings are split pillow block housings consisting of a cap and base. SAF housings have two or four holes cast into the base for attachment bolts. SAF housings are available in two designs depending on the series. SAF housings in the 2(00) and 5(00) series follow the M5 design, while housings in the 3(00) and 6(00) series follow the A design.

The split plummer block housings are typically used with self-aligning ball bearings, spherical roller bearings or CARB toroidal roller bearings fitted on straight or stepped shafts; the bearings can be mounted on adapter or withdrawal sleeves or directly on cylindrical shaft seats.

SAF and housings are made of grey cast iron. For applications where extra strength is needed, SAF housings are also available in cast steel, designation SAFS. SAF housings are also available in ductile iron (spheroidal graphite cast iron), designation SAFD.

Characteristics

Series: FSAF

Manufacturer ID	Outer dimension bearing	Length	Height	Shaft height	Centre distance of mounting holes	Housing material	Article
	mm	mm	mm	mm	mm		
FSAF 517	150					Grey cast iron	13249070
FSAF 218	160	349.25	192.6	101.6	279.4	Grey cast iron	12053667
FSAF 520	180	387.35	217.488	114.3	314.325	Grey cast iron	23764799

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

PR1579278047631541_EN_11.05.2024