



ASCO Solenoid valve 2/2 Type: 32003 series 256C stainless steel normally closed

Characteristics

Function: Normally closed (NC)

Actuation: Direct-acting

Electrical connection: Plug EN 175301-803 type A

Max. viscosity: 40 mm²/s

Housing material: Stainless steel

Sealing: FPM (FKM)

Material coil housing: PPS

Material shorting ring: Copper

Working time: 100 %

Level of protection (IP value): IP67

Explosion-proof: No

Medium temperature: From 0 °C to 130 °C

Ambient temperature: From -10 °C to 60 °C

Application

- Slightly aggressive gases.
- Liquids.

Technical Information

- Standard FPM seal.
- Conversion from AC to DC coil possible.

Size process connection	Process connection	Orifice	Kvs value	Minimum pressure difference	Maximum pressure difference	Coil type	Supply voltage	Power	Emergency manual operation	Article
		mm	m ³ /h	bar	bar					
1/8" (6)	Internal thread (BSPP)	1.2	0.051	0	20	533534-001	24V DC	3.5 W	Yes	14335145
1/8" (6)	Internal thread (BSPP)	1.6	0.08	0	30	533593-011	24V AC	3 W / 4.5 VA	Yes	14335147
1/8" (6)	Internal thread (BSPP)	1.6	0.08	0	12	533534-001	24V DC	3.5 W	Yes	14335148
1/8" (6)	Internal thread (BSPP)	1.6	0.08	0	30	533534-003	230V AC	3 W / 4.5 VA	Yes	14335146
1/8" (6)	Internal thread (BSPP)	2	0.12	0	6	533534-001	24V DC	3.5 W	Yes	14335149
1/8" (6)	Internal thread (BSPP)	2.4	0.14	0	4		12V DC	3.5 W	Yes	14335150
1/8" (6)	Internal thread (BSPP)	2.4	0.14	0	13	533593-011	24V AC	3 W / 4.5 VA	Yes	14335152
1/8" (6)	Internal thread (BSPP)	2.4	0.14	0	4	533534-001	24V DC	3.5 W	Yes	14335153
1/8" (6)	Internal thread (BSPP)	2.4	0.14	0	13	533534-003	230V AC	3 W / 4.5 VA	Yes	14335151
1/4" (8)	Internal thread (BSPP)	2.4	0.18	0	18	533534-002	24V DC	5 W	None	14335158

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.