



FESTO Ball valve Series: VZBM Brass Internal thread (BSPP) PN25/40/50

Characteristics

Series: VZBM

Construction type: 2-way

Housing construction: 2-part

Housing material: Brass

Material quality: CW617N

Surface protection: Nickel-plated

Connection: Internal thread (BSPP)

Top flange standard: ISO 5211

Nominal inner diameter	Pressure rating	Manual operation	Mounting flange	Mounting flange 2	Material ball	Seat material	Spindle material	Minimum medium temperature (continuous) °C	Maximum medium temperature (continuous) °C	Article
1/4" [8]	PN40	Bare stem	F03		Brass chromium-plated	PTFE	Brass	-20	130	14168333
1/4" [8]	PN50	Handle			Brass chromium-plated	PTFE	Brass	-20	130	14168326
3/8" [10]	PN40	Bare stem	F03		Brass chromium-plated	PTFE	Brass	-20	130	14168332
3/8" [10]	PN50	Handle			Brass chromium-plated	PTFE	Brass	-20	130	14168327
1/2" [15]	PN25	Bare stem	F03		Brass chromium-plated	PTFE	Brass	-20	130	14168334
1/2" [15]	PN50	Handle			Brass chromium-plated	PTFE	Brass	-20	130	14168328
3/4" [20]	PN25	Bare stem	F03		Brass chromium-plated	PTFE	Brass	-20	130	14168337
3/4" [20]	PN50	Handle			Brass chromium-plated	PTFE	Brass	-20	130	14168329
1" [25]	PN25	Bare stem	F03		Brass chromium-plated	PTFE	Brass	-20	130	14168339
1" [25]	PN40	Handle			Brass chromium-plated	PTFE	Brass	-20	130	14168336
1.1/4" [32]	PN25	Bare stem	F03		Brass chromium-plated	PTFE	Brass	-20	130	14168345
1.1/4" [32]	PN40	Handle			Brass chromium-plated	PTFE	Brass	-20	130	14168340
1.1/2" [40]	PN25	Bare stem	F03	F05	Brass chromium-plated	PTFE	Brass	-20	130	14168349
1.1/2" [40]	PN40	Handle			Brass chromium-plated	PTFE	Brass	-20	130	14168346

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal inner diameter	Pressure rating	Manual operation	Mounting flange	Mounting flange 2	Material ball	Seat material	Spindle material	Minimum medium temperature (continuous) °C	Maximum medium temperature (continuous) °C	Article
2" [50]	PN25	Bare stem	F03	F05	Brass chromium-plated	PTFE	Brass	-20	130	14168357

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.