



GF Ball valve Series: 546 PVC-C Glued sleeve PN10/16

Characteristics

Series: 546

Norm: EN (DIN)

Construction type: 2-way

Housing construction: 3-part

Housing material: PVC-C

Connection: Glued sleeve

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Manual operation	Material ball	Seat material	Primary spindle seal material	Secondary spindle seal material	Body seal	Article
DN10	16	PN16	Manufacturer standard	Handle	PVC-C	PTFE	EPDM	EPDM	EPDM	11270567
DN15	20	PN16	Manufacturer standard	Handle	PVC-C	PTFE	FPM (FKM)	FPM (FKM)	FPM (FKM)	11270537
DN15	20	PN16	Manufacturer standard	Handle	PVC-C	PTFE	EPDM	EPDM	EPDM	11270568
DN20	25	PN16	Manufacturer standard	Handle	PVC-C	PTFE	EPDM	EPDM	EPDM	11270569
DN25	32	PN16	Manufacturer standard	Handle	PVC-C	PTFE	FPM (FKM)	FPM (FKM)	FPM (FKM)	11270563
DN25	32	PN16	Manufacturer standard	Handle	PVC-C	PTFE	EPDM	EPDM	EPDM	11270570
DN32	40	PN16	Manufacturer standard	Handle	PVC-C	PTFE	EPDM	EPDM	EPDM	11270571
DN40	50	PN16	Manufacturer standard	Handle	PVC-C	PTFE	EPDM	EPDM	EPDM	11270572
DN50	63	PN16	Manufacturer standard	Handle	PVC-C	PTFE	EPDM	EPDM	EPDM	11270573
DN65	75	PN16	Manufacturer standard	Handle	PVC-C	PTFE	EPDM	EPDM	EPDM	11528804
DN100	110	PN16	Manufacturer standard	Handle	PVC-C	PTFE	EPDM	EPDM	EPDM	11654749

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.