


Rubber stop NR

Rubber stop made of natural rubber with countersunk threadhole, as an anti-slip machinefoot and buffer, for electric apparatus and other equipment. Hardness: 60 Shore A.



Size table:

D mm	d mm	e mm	H mm	s mm
15	3	7	7	3
16	1.5	5	8	3
12	3	7	8.5	4
19	3	7	9.5	5
22	4	9	10	4.5
21	2.5	6.5	11	6
25	5	8	11	6
29	5	10	11	5
16	4	8	15	7

Height mm	Material	D mm	d mm	e mm	H mm	s mm	Colour	Article
7	NR	15	3	7	7	3	White	12730344
7	NR	15	3	7	7	3	Black	12730343
8	NR	16	1.5	5	8	3	White	12730346
8	NR	16	1.5	5	8	3	Black	12730345
8.5	NR	12	3	7	8.5	4	White	12730342
8.5	NR	12	3	7	8.5	4	Black	12730341
9.5	NR	19	3	7	9.5	5	White	12730350
9.5	NR	19	3	7	9.5	5	Black	12730349
10	NR	22	4	9	10	4.5	Grey	12730354
10	NR	22	4	9	10	4.5	Black	12730353
11	NR	21	2.5	6.5	11	6	White	12730352
11	NR	21	2.5	6.5	11	6	Black	12730351
11	NR	25	5	8	11	6	Black	12730355

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Height mm	Material	D mm	d mm	e mm	H mm	s mm	Colour	Article
11	NR	29	5	10	11	5	White	12730358
11	NR	29	5	10	11	5	Black	12730357
11	NR	25	5	8	11	6	White	12730356
15	NR	16	4	8	15	7	Black	12730347

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.