## **Protective cap soft PVC**

Protective cap of soft PVC 65Sh A, lead and cadmium free, resistant against many chemicals, ageing-and weather-resistant. Fire behaviour is self damping, dielectric strength is 20kV/mm. Tolerances: ID ±1,5mm, wall thickness ±0,25mm. Temperature range -20 till +85°C. Colour: black.



## Size table:

н
mm
10
20
15

Н	Inner diameter	Wall thickness	Colour	Execution	Article
mm	mm	mm			
10	3.5	1	Black	Self-extinguishing	12730487
10	3	1	Black	Self-extinguishing	12730486
10	2.5	1	Black	Self-extinguishing	12730485
20	10	1.5	Black	Self-extinguishing	12730494
20	9	1.5	Black	Self-extinguishing	12730493
20	8	1.5	Black	Self-extinguishing	12730492
15	7	1.5	Black	Self-extinguishing	12730491
15	6	1.5	Black	Self-extinguishing	12730490
15	5	1.5	Black	Self-extinguishing	12730489
15	4	1.5	Black	Self-extinguishing	12730488

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

