

HAVIT SAE 90° flange adapter BSP-60° WFG

Supplied with two flange halves, screw set and O-ring.





Characteristics

Series: WFG

Flange type: SAE 90° flange adapter

Material: Steel

Thread form: BSP 60° cone



Size table:

Pressure class	SAE flange size	A	B1	B2	C	D	E	F1	F2
psi	in	mm	mm	mm	mm	mm	mm	mm	mm
3000	1/2	G 1/2"	11	11	38.1	54	17.5	63	46
3000	3/4	G 3/4"	16.7	19	47.6	65	22.3	76	52
3000	1	G 1"	22.2	25	52.4	70	26.2	81.5	59
3000	1.1/4	G 1.1/4"	28.6	24	58.7	79	30.2	94.5	73
3000	1.1/2	G 1.1/2"	33.3	36	69.9	94	35.7	117.5	83
6000	1/2	G 1/2"	11	12	40.5	56	18.2	64	48
6000	3/4	G 3/4"	16.7	17	50.8	71	23.8	80	60
6000	1	G 1"	22.2	24	57.2	81	27.8	94	70
6000	1.1/4	G 1.1/4"	28.6	31	66.6	95	31.8	104	78
6000	1.1/2	G 1.1/2"	33.3	36	79.3	113	36.5	123.5	95

Pressure class	SAE flange size	Surface protection	Thread size	Max. operation pressure	Article
psi	in			bar	
3000	1/2	Untreated	G 1/2"	350	14312653
3000	3/4	Untreated	G 3/4"	350	14312742
3000	1	Untreated	G 1"	320	14312829
3000	1.1/4	Untreated	G 1.1/4"	280	14312975
3000	1.1/2	Untreated	G 1.1/2"	210	14313060
6000	1/2	Untreated	G 1/2"	420	14313115
6000	3/4	Untreated	G 3/4"	420	14313192
6000	1	Untreated	G 1"	420	14313252
6000	1.1/4	Untreated	G 1.1/4"	420	14313327
6000	1.1/2	Untreated	G 1.1/2"	420	14313387

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.