



ULTRAFILTER Cartridge filter body Series: PF-EG Stainless steel External thread DIN 11851

Characteristics

Series: PF-EG

Housing material: Stainless steel

Internal element connection: Code 7

Connection: External thread DIN 11851

Pressure rating: PN16

With filter element: No

Application

- Liquids.
- Horizontal piping.
- Suction and delivery piping.
- Recommended in: Food & Beverages, Food primary processes [contact with food]

Technical Information

- Stainless steel filter housing 316, stained and passivated.
- Suitable for mounting 1 or more 5 inch/10 inch/20 inch/30 inch/40 inch filter cartridges.
- Maximum operating pressure 8bar.
- Element connection according to code 7.
- Connections with male thread DIN11851.
- EPM seal.

Execution

- Cover can be closed with clamping strip and turnbuckle.
- Fitted with drain and bleed screw.

Approval

- Suitable for PED 2014/68/EU Art. 4.3 [SEP].
- EC1935.

Options

- Filter housings in various dimensions and designs.
- Various element connections.
- Various seals.

Type	Flow rate table			
	Flow rate l/min	Connection DN	Weight without element kg	Size Code 7
0012	12	DN25	4	5/3
0025	25	DN25	5	10/3
0050	50	DN25	6	20/3
0075	75	DN25	7	30/3
0080	75	DN40	11	10/3
0150	150	DN40	14	20/3
0225	225	DN40	17	30/3
0250	250	DN50	29	20/3
0375	375	DN50	32	30/3
0450	450	DN65	45	20/3
0675	675	DN65	50	30/3
*Flow rate is based on water and filter cartridge type PF-PP				

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Body size	Material quality	Nominal inner diameter	Max. operating pressure bar	Article
0012	SS316	DN25	8	14494951
0025	SS316	DN25	8	14494952
0050	SS316	DN25	8	14494953
0075	SS316	DN25	8	14494954
0080	SS316	DN40	8	14494955
0150	SS316	DN40	8	14494956
0225	SS316	DN40	8	14494957
0250	SS316	DN50	8	14494958
0375	SS316	DN50	8	14494959
0450	SS316	DN65	8	14494960
0675	SS316	DN65	8	14494961

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.