



STAUFF Push-to-connect coupling Flat-Face series FF

Flat Face Push-to-Connect Couplings of the FF Series consist of a male tip and a female body and are used for quick and easy connection (push) and disconnection of tubes, pipes and hoses by hand, i.e. without tools.

The Series was developed according to ISO 16028 in the following nominal sizes 06, 10, 12, 16, 19, 25, 38 [1/4" - 1 1/2"] and can be connected under pressure with male tips of the FC series.

Characteristics

Series: FF

Material: Steel

Surface protection: Zinc-Nickel

Valve shape: Flat face

Minimum medium temperature (continuous): -25 °C

Maximum medium temperature (continuous): 100 °C

Standard: ISO 16028

Connectable under residual pressure: Yes

Application

- Agricultural and forestry machinery, construction machinery, industrial hydraulic

Technical Information

Connect under pressure:

- not allowed, male tip series FC up to the max. working pressure allowed

Execution

Flat Face quick release couplings have the following advantages:

- The flat face valve design reduces the risk of leakage and wear
- Reducing the risk of contaminants from entering the system
- Powerful flow characteristics with minimal pressure drop

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Coupling (female)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	400	0.01	24	NBR/PTFE	14508169
Coupling (female)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	400	0.01	24	NBR/PTFE	14508167
Coupling (female)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	400	0.01	24	FKM/PTFE	14508170
Coupling (female)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	400	0.01	24	NBR/PTFE	14508168
Coupling (female)	1	6.3	1/4"	Cutting ring connection	10L - M16x1.5	400	0.01	24	NBR/PTFE	14508172
Coupling (female)	1	6.3	1/4"	Cutting ring connection	10L - M16x1.5	400	0.01	24	NBR/PTFE	14508171
Coupling (female)	1	6.3	1/4"	External thread	1/4" BSP cyl.	400	0.01	24	NBR/PTFE	14508173
Coupling (female)	1	6.3	1/4"	Internal thread	1/4" BSP cyl.	400	0.01	24	FKM/PTFE	14508174
Coupling (female)	1	6.3	1/4"	Internal thread	1/4" BSP cyl.	400	0.01	24	NBR/PTFE	14229970
Coupling (female)	1	6.3	1/4"	Internal thread	1/4" NPT	400	0.01	24	NBR/PTFE	14508176
Coupling (female)	1	6.3	1/4"	Internal thread	3/8" BSP cyl.	400	0.01	24	NBR/PTFE	14508175
Coupling (female)	1	6.3	1/4"	Internal thread	9/16-18 UNF	400	0.01	24	NBR/PTFE	14229971
Coupling (female)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	350	0.015	46	NBR/PTFE	14508201
Coupling (female)	2	10	3/8"	Cutting ring connection	8L - M14x1.5	350	0.015	46	NBR/PTFE	14508202
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	350	0.015	46	NBR/PTFE	13854447
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	350	0.015	46	NBR/PTFE	14229974
Coupling (female)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	350	0.015	46	NBR/PTFE	14508203

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Max. 200 articles in the table										
Coupling (female)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	350	0.015	46	NBR/PTFE	13854449
Coupling (female)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	350	0.015	46	NBR/PTFE	14011581
Coupling (female)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	350	0.015	46	NBR/PTFE	14508205
Coupling (female)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	350	0.015	46	NBR/PTFE	14508204
Coupling (female)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	350	0.015	46	NBR/PTFE	13854321
Coupling (female)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	350	0.015	46	NBR/PTFE	14229975
Coupling (female)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	350	0.015	46	NBR/PTFE	14229976
Coupling (female)	2	10	3/8"	Cutting ring connection	15L - M22x1.5	350	0.015	46	NBR/PTFE	14508208
Coupling (female)	2	10	3/8"	Cutting ring connection	15L - M22x1.5	350	0.015	46	NBR/PTFE	13854450
Coupling (female)	2	10	3/8"	Cutting ring connection	15L - M22x1.5	350	0.015	46	NBR/PTFE	14508207
Coupling (female)	2	10	3/8"	Cutting ring connection	15L - M22x1.5	350	0.015	46	NBR/PTFE	14508206
Coupling (female)	2	10	3/8"	Cutting ring connection	15L - M22x1.5	350	0.015	46	NBR/PTFE	14229977
Coupling (female)	2	10	3/8"	Cutting ring connection	16S - M24x1.5	350	0.015	46	NBR/PTFE	14229978
Coupling (female)	2	10	3/8"	Cutting ring connection	16S - M24x1.5	350	0.015	46	NBR/PTFE	14508209
Coupling (female)	2	10	3/8"	Cutting ring connection	16S - M24x1.5	350	0.015	46	NBR/PTFE	14508210
Coupling (female)	2	10	3/8"	External thread	3/4"-16 UNF (JIC)	350	0.015	46	NBR/PTFE	14508214
Coupling (female)	2	10	3/8"	External thread	3/8" BSP cyl.	350	0.015	46	NBR/PTFE	14508211
Coupling (female)	2	10	3/8"	Internal thread	1/2" BSP cyl.	350	0.015	46	NBR/PTFE	14508213
Coupling (female)	2	10	3/8"	Internal thread	1/2" BSP cyl.	350	0.015	46	NBR/PTFE	13854443
Coupling (female)	2	10	3/8"	Internal thread	1/2" NPT	350	0.015	46	NBR/PTFE	14508218
Coupling (female)	2	10	3/8"	Internal thread	1/2" NPT	350	0.015	46	FKM/PTFE	14508219
Coupling (female)	2	10	3/8"	Internal thread	3/4-16 UNF	350	0.015	46	NBR/PTFE	14508221
Coupling (female)	2	10	3/8"	Internal thread	3/8" BSP cyl.	350	0.015	46	NBR/PTFE	13854441
Coupling (female)	2	10	3/8"	Internal thread	3/8" BSP cyl.	350	0.015	46	FKM/PTFE	14508212
Coupling (female)	2	10	3/8"	Internal thread	3/8" NPT	350	0.015	46	NBR/PTFE	14508217
Coupling (female)	2	10	3/8"	Internal thread	9/16-18 UNF	350	0.015	46	NBR/PTFE	14508220
Coupling (female)	2	10	3/8"	Internal thread	M 18x1.5 OR	350	0.015	46	NBR/PTFE	14508215
Coupling (female)	2	10	3/8"	Internal thread	M 22x1.5 OR	350	0.015	46	NBR/PTFE	14508216
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	350	0.02	90	NBR/PTFE	13854327
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	350	0.02	90	NBR/PTFE	13854330
Coupling (female)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	350	0.02	90	NBR/PTFE	14508247
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	350	0.02	90	NBR/PTFE	13854328
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	350	0.02	90	NBR/PTFE	14508250
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	350	0.02	90	NBR/PTFE	14508249

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Max. 200 articles in the table										
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	350	0.02	90	NBR/PTFE	14508248
Coupling (female)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	350	0.02	90	NBR/PTFE	13854331
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	350	0.02	90	NBR/PTFE	13854332
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	350	0.02	90	NBR/PTFE	14229983
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	350	0.02	90	NBR/PTFE	14508252
Coupling (female)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	350	0.02	90	NBR/PTFE	14508251
Coupling (female)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	350	0.02	90	NBR/PTFE	13854329
Coupling (female)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	350	0.02	90	NBR/PTFE	14508253
Coupling (female)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	350	0.02	90	NBR/PTFE	14508254
Coupling (female)	3	12.5	1/2"	Cutting ring connection	20S - M30x2.0	350	0.02	90	NBR/PTFE	14508255
Coupling (female)	3	12.5	1/2"	Cutting ring connection	20S - M30x2.0	350	0.02	90	NBR/PTFE	14508256
Coupling (female)	3	12.5	1/2"	Cutting ring connection	22L - M30x2.0	350	0.02	90	NBR/PTFE	14508257
Coupling (female)	3	12.5	1/2"	Cutting ring connection	22L - M30x2.0	350	0.02	90	NBR/PTFE	14508258
Coupling (female)	3	12.5	1/2"	Cutting ring connection	22L - M30x2.0	350	0.02	90	NBR/PTFE	13854481
Coupling (female)	3	12.5	1/2"	External thread	1"-14 UN (ORFS)	350	0.02	90	NBR/PTFE	14508265
Coupling (female)	3	12.5	1/2"	External thread	7/8"-14 UNF (JIC)	350	0.02	90	NBR/PTFE	14508262
Coupling (female)	3	12.5	1/2"	Internal thread	1.1/16-12 UN	350	0.02	90	NBR/PTFE	14508268
Coupling (female)	3	12.5	1/2"	Internal thread	1.1/16-12 UN	350	0.02	90	NBR/PTFE	14229985
Coupling (female)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	350	0.02	90	NBR/PTFE	13854326
Coupling (female)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	350	0.02	90	NBR/PTFE	13854472
Coupling (female)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	350	0.02	90	FKM/PTFE	14508260
Coupling (female)	3	12.5	1/2"	Internal thread	1/2" NPT	350	0.02	90	NBR/PTFE	14508263
Coupling (female)	3	12.5	1/2"	Internal thread	3/4" BSP cyl.	350	0.02	90	FKM/PTFE	14508261
Coupling (female)	3	12.5	1/2"	Internal thread	3/4" BSP cyl.	350	0.02	90	NBR/PTFE	14175641
Coupling (female)	3	12.5	1/2"	Internal thread	3/4" NPT	350	0.02	90	NBR/PTFE	14508264
Coupling (female)	3	12.5	1/2"	Internal thread	3/4-16 UNF	350	0.02	90	NBR/PTFE	14508266
Coupling (female)	3	12.5	1/2"	Internal thread	7/8-14 UNF	350	0.02	90	NBR/PTFE	14229984
Coupling (female)	3	12.5	1/2"	Internal thread	7/8-14 UNF	350	0.02	90	FKM/PTFE	14508267
Coupling (female)	4A	16	5/8"	Cutting ring connection	15L - M22x1.5	350	0.02	148	NBR/PTFE	14508284
Coupling (female)	4A	16	5/8"	Cutting ring connection	15L - M22x1.5	350	0.02	148	NBR/PTFE	14508283
Coupling (female)	4A	16	5/8"	Cutting ring connection	18L - M26x1.5	350	0.02	148	NBR/PTFE	14508286
Coupling (female)	4A	16	5/8"	Cutting ring connection	18L - M26x1.5	350	0.02	148	NBR/PTFE	14508285
Coupling (female)	4A	16	5/8"	Cutting ring connection	20S - M30x2.0	350	0.02	148	NBR/PTFE	14508287
Coupling (female)	4A	16	5/8"	Cutting ring connection	22L - M30x2.0	350	0.02	148	NBR/PTFE	14229991

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Max. 200 articles in the table										
Coupling (female)	4A	16	5/8"	Cutting ring connection	22L - M30x2.0	350	0.02	148	NBR/PTFE	14508288
Coupling (female)	4A	16	5/8"	Cutting ring connection	25S - M36x2.0	350	0.02	148	NBR/PTFE	14508290
Coupling (female)	4A	16	5/8"	Cutting ring connection	25S - M36x2.0	350	0.02	148	NBR/PTFE	14508289
Coupling (female)	4A	16	5/8"	Internal thread	1.1/16-12 UN	350	0.02	148	NBR/PTFE	14229995
Coupling (female)	4A	16	5/8"	Internal thread	1.1/16-12 UN	350	0.02	148	FKM/PTFE	14508292
Coupling (female)	4A	16	5/8"	Internal thread	1/2" NPT	350	0.02	148	NBR/PTFE	13856154
Coupling (female)	4A	16	5/8"	Internal thread	1" BSP cyl.	350	0.02	148	NBR/PTFE	14229993
Coupling (female)	4A	16	5/8"	Internal thread	3/4" BSP cyl.	350	0.02	148	NBR/PTFE	14229992
Coupling (female)	4A	16	5/8"	Internal thread	3/4" BSP cyl.	350	0.02	148	FKM/PTFE	14508291
Coupling (female)	4A	16	5/8"	Internal thread	3/4" NPT	350	0.02	148	NBR/PTFE	14229994
Coupling (female)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	350	0.032	212	NBR/PTFE	14508305
Coupling (female)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	350	0.032	212	NBR/PTFE	14508304
Coupling (female)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	350	0.032	212	NBR/PTFE	14508307
Coupling (female)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	350	0.032	212	NBR/PTFE	14508306
Coupling (female)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	350	0.032	212	NBR/PTFE	14508309
Coupling (female)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	350	0.032	212	NBR/PTFE	14508308
Coupling (female)	4	19	3/4"	Cutting ring connection	25S - M36x2.0	350	0.032	212	NBR/PTFE	14508310
Coupling (female)	4	19	3/4"	Cutting ring connection	28L - M36x2.0	350	0.032	212	NBR/PTFE	14508312
Coupling (female)	4	19	3/4"	Cutting ring connection	28L - M36x2.0	350	0.032	212	NBR/PTFE	14508311
Coupling (female)	4	19	3/4"	Internal thread	1.1/16-12 UN	350	0.032	212	NBR/PTFE	14229999
Coupling (female)	4	19	3/4"	Internal thread	1.5/16-12 UNF	350	0.032	212	NBR/PTFE	13854519
Coupling (female)	4	19	3/4"	Internal thread	1" BSP cyl.	350	0.032	212	NBR/PTFE	13854514
Coupling (female)	4	19	3/4"	Internal thread	1" BSP cyl.	350	0.032	212	FKM/PTFE	14508313
Coupling (female)	4	19	3/4"	Internal thread	1" NPT	350	0.032	212	NBR/PTFE	14508315
Coupling (female)	4	19	3/4"	Internal thread	3/4" BSP cyl.	350	0.032	212	NBR/PTFE	13854512
Coupling (female)	4	19	3/4"	Internal thread	3/4" NPT	350	0.032	212	NBR/PTFE	14508314
Coupling (female)	5	25	1"	Internal thread	1.1/4" BSP cyl.	260	0.03	378	FKM/PTFE	14508331
Coupling (female)	5	25	1"	Internal thread	1.1/4" BSP cyl.	260	0.03	378	NBR/PTFE	14230001
Coupling (female)	6	38	1.1/2"	Internal thread	1.1/2" BSP cyl.	300	0.155	684	NBR/PTFE/PU	14230006
Plug (male)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	400	0.01	24	NBR/PTFE/PU	14508179
Plug (male)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	400	0.01	24	FKM/PTFE	14508178
Plug (male)	1	6.3	1/4"	Cutting ring connection	8L - M14x1.5	400	0.01	24	NBR/PTFE/PU	14508177
Plug (male)	1	6.3	1/4"	Cutting ring connection	10L - M16x1.5	400	0.01	24	NBR/PTFE/PU	14508181
Plug (male)	1	6.3	1/4"	Cutting ring connection	10L - M16x1.5	400	0.01	24	NBR/PTFE/PU	14508180

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Max. 200 articles in the table										
Plug (male)	1	6.3	1/4"	External thread	1/4" BSP cyl.	400	0.01	24	NBR/PTFE/PU	14508182
Plug (male)	1	6.3	1/4"	Internal thread	1/4" BSP cyl.	400	0.01	24	FKM/PTFE	14508183
Plug (male)	1	6.3	1/4"	Internal thread	1/4" BSP cyl.	400	0.01	24	NBR/PTFE/PU	14229972
Plug (male)	1	6.3	1/4"	Internal thread	1/4" NPT	400	0.01	24	NBR/PTFE/PU	14508184
Plug (male)	1	6.3	1/4"	Internal thread	9/16-18 UNF	400	0.01	24	NBR/PTFE/PU	14229973
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	350	0.015	46	NBR/PU	14229979
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	350	0.015	46	NBR/PU	14508222
Plug (male)	2	10	3/8"	Cutting ring connection	10L - M16x1.5	350	0.015	46	NBR/PU	13854464
Plug (male)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	350	0.015	46	NBR/PU	13854462
Plug (male)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	350	0.015	46	NBR/PU	14508224
Plug (male)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	350	0.015	46	NBR/PU	14508223
Plug (male)	2	10	3/8"	Cutting ring connection	12L - M18x1.5	350	0.015	46	NBR/PU	13854322
Plug (male)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	350	0.015	46	NBR/PU	14229980
Plug (male)	2	10	3/8"	Cutting ring connection	12S - M20x1.5	350	0.015	46	NBR/PU	14229981
Plug (male)	2	10	3/8"	Cutting ring connection	15L - M22x1.5	350	0.015	46	NBR/PU	13854463
Plug (male)	2	10	3/8"	Cutting ring connection	15L - M22x1.5	350	0.015	46	NBR/PU	13854466
Plug (male)	2	10	3/8"	Cutting ring connection	15L - M22x1.5	350	0.015	46	NBR/PU	14508225
Plug (male)	2	10	3/8"	Cutting ring connection	16S - M24x1.5	350	0.015	46	NBR/PU	14229982
Plug (male)	2	10	3/8"	Cutting ring connection	18L - M26x1.5	350	0.015	46	NBR/PU	14508226
Plug (male)	2	10	3/8"	External thread	3/4"-16 UNF (JIC)	350	0.015	46	NBR/PU	14508230
Plug (male)	2	10	3/8"	External thread	3/8" BSP cyl.	350	0.015	46	NBR/PU	14508227
Plug (male)	2	10	3/8"	Internal thread	1/2" BSP cyl.	350	0.015	46	FKM/PTFE	14508229
Plug (male)	2	10	3/8"	Internal thread	1/2" BSP cyl.	350	0.015	46	NBR/PU	13854457
Plug (male)	2	10	3/8"	Internal thread	1/2" NPT	350	0.015	46	NBR/PU	14508232
Plug (male)	2	10	3/8"	Internal thread	1/2" NPT	350	0.015	46	FKM/PTFE	14508233
Plug (male)	2	10	3/8"	Internal thread	3/4" - 16 UNF	350	0.015	46	NBR/PU	13854460
Plug (male)	2	10	3/8"	Internal thread	3/8" BSP cyl.	350	0.015	46	NBR/PU	13854455
Plug (male)	2	10	3/8"	Internal thread	3/8" BSP cyl.	350	0.015	46	FKM/PTFE	14508228
Plug (male)	2	10	3/8"	Internal thread	3/8" NPT	350	0.015	46	NBR/PU	14508231
Plug (male)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	350	0.02	90	NBR/PU	13854335
Plug (male)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	350	0.02	90	NBR/PU	13854338
Plug (male)	3	12.5	1/2"	Cutting ring connection	12L - M18x1.5	350	0.02	90	NBR/PU	14508269
Plug (male)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	350	0.02	90	NBR/PU	14229986
Plug (male)	3	12.5	1/2"	Cutting ring connection	15L - M22x1.5	350	0.02	90	NBR/PU	14508270

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure	Spillage	Max. flow rate	Sealing	Article
		mm				bar	ml	l/min		Max. 200 articles in the table
Plug (male)	3	12.5	1/2"	Cutting ring connection	16S - M24x1.5	350	0.02	90	NBR/PU	14508271
Plug (male)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	350	0.02	90	NBR/PU	14229987
Plug (male)	3	12.5	1/2"	Cutting ring connection	18L - M26x1.5	350	0.02	90	NBR/PU	14508272
Plug (male)	3	12.5	1/2"	Cutting ring connection	20S - M30x2.0	350	0.02	90	NBR/PU	14508273
Plug (male)	3	12.5	1/2"	Cutting ring connection	20S - M30x2.0	350	0.02	90	NBR/PU	14229988
Plug (male)	3	12.5	1/2"	Cutting ring connection	22L - M30x2.0	350	0.02	90	NBR/PU	14508274
Plug (male)	3	12.5	1/2"	External thread	1"-14 UN (ORFS)	350	0.02	90	NBR/PU	14508279
Plug (male)	3	12.5	1/2"	Internal thread	1.1/16-12 UN	350	0.02	90	NBR/PU	14229990
Plug (male)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	350	0.02	90	FKM/PTFE	14508275
Plug (male)	3	12.5	1/2"	Internal thread	1/2" BSP cyl.	350	0.02	90	NBR/PU	13854483
Plug (male)	3	12.5	1/2"	Internal thread	1/2" NPT	350	0.02	90	NBR/PU	14508277
Plug (male)	3	12.5	1/2"	Internal thread	3/4" - 16 UNF	350	0.02	90	NBR/PU	13854488
Plug (male)	3	12.5	1/2"	Internal thread	3/4" BSP cyl.	350	0.02	90	NBR/PU	13854485
Plug (male)	3	12.5	1/2"	Internal thread	3/4" BSP cyl.	350	0.02	90	FKM/PTFE	14508276
Plug (male)	3	12.5	1/2"	Internal thread	3/4" NPT	350	0.02	90	NBR/PU	14508278
Plug (male)	3	12.5	1/2"	Internal thread	7/8-14 UNF	350	0.02	90	FKM/PTFE	14508281
Plug (male)	3	12.5	1/2"	Internal thread	7/8-14 UNF	350	0.02	90	NBR/PU	14229989
Plug (male)	4A	16	5/8"	Cutting ring connection	15L - M22x1.5	350	0.02	148	NBR/PU	14508293
Plug (male)	4A	16	5/8"	Cutting ring connection	16S - M24x1.5	350	0.02	148	NBR/PU	14508294
Plug (male)	4A	16	5/8"	Cutting ring connection	22L - M30x2.0	350	0.02	148	NBR/PU	14508295
Plug (male)	4A	16	5/8"	Cutting ring connection	25S - M36x2.0	350	0.02	148	NBR/PU	14508296
Plug (male)	4A	16	5/8"	Internal thread	1.1/16-12 UN	350	0.02	148	NBR/PU	14229998
Plug (male)	4A	16	5/8"	Internal thread	1.1/16-12 UN	350	0.02	148	FKM/PTFE	14508299
Plug (male)	4A	16	5/8"	Internal thread	1" BSP cyl.	350	0.02	148	NBR/PU	14508298
Plug (male)	4A	16	5/8"	Internal thread	3/4" BSP cyl.	350	0.02	148	FKM/PTFE	14508297
Plug (male)	4A	16	5/8"	Internal thread	3/4" BSP cyl.	350	0.02	148	NBR/PU	14229996
Plug (male)	4A	16	5/8"	Internal thread	3/4" NPT	350	0.02	148	NBR/PU	14229997
Plug (male)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	350	0.032	212	NBR/PU	14508317
Plug (male)	4	19	3/4"	Cutting ring connection	18L - M26x1.5	350	0.032	212	NBR/PU	14508316
Plug (male)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	350	0.032	212	NBR/PU	14508318
Plug (male)	4	19	3/4"	Cutting ring connection	20S - M30x2.0	350	0.032	212	NBR/PU	13854533
Plug (male)	4	19	3/4"	Cutting ring connection	22L - M30x2.0	350	0.032	212	NBR/PU	14508319
Plug (male)	4	19	3/4"	Cutting ring connection	25S - M36x2.0	350	0.032	212	NBR/PU	14508320
Plug (male)	4	19	3/4"	Cutting ring connection	28L - M36x2.0	350	0.032	212	NBR/PU	14508322

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Plug (male)	4	19	3/4"	Cutting ring connection	28L - M36x2.0	350	0.032	212	NBR/PU	14508321
Plug (male)	4	19	3/4"	Cutting ring connection	30S - M42x2.0	350	0.032	212	NBR/PU	14508323
Plug (male)	4	19	3/4"	Internal thread	1.1/16-12 UN	350	0.032	212	NBR/PU	14508327
Plug (male)	4	19	3/4"	Internal thread	1.5/16-12 UN	350	0.032	212	NBR/PU	14230000
Plug (male)	4	19	3/4"	Internal thread	1" BSP cyl.	350	0.032	212	FKM/PTFE	14508324
Plug (male)	4	19	3/4"	Internal thread	1" BSP cyl.	350	0.032	212	NBR/PU	13854525
Plug (male)	4	19	3/4"	Internal thread	3/4" BSP cyl.	350	0.032	212	NBR/PU	13854523
Plug (male)	4	19	3/4"	Internal thread	3/4" NPT	350	0.032	212	NBR/PU	14508325
Plug (male)	5	25	1"	Internal thread	1.1/4" BSP cyl.	260	0.03	378	NBR/PU	14230003
Plug (male)	5	25	1"	Internal thread	1" BSP cyl.	260	0.03	378	NBR/PU	14230002
Plug (male)	6	38	1.1/2"	Internal thread	1.1/2" BSP cyl.	300	0.155	684	NBR/PTFE	14230007
Plug (male)	6	38	1.1/2"	Internal thread	1.7/8-12 UN	300	0.155	684	NBR/PTFE	14230008

Max. 200 articles in the table

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.