

STAUFF Push-to-connect coupling Flat-Face series HD



Characteristics

Series: HD

Material: Steel

Surface protection: Zinc coated

Valve shape: Flat face

Minimum medium temperature (continuous): -35 °C

Maximum medium temperature (continuous): 130 °C

Connectable under residual pressure: No

Execution

Flat Face quick release couplings have the following advantages:

- The flat face valve design reduces the risk of leakage and wear
- Reducing the risk of contaminants from entering the system
- Powerful flow characteristics with minimal pressure drop

Application

- Rescue and tensioning hydraulics

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Coupling (female)	1	6.3	1/4"	Internal thread	1/4" BSP cyl.	1500	0.008	6	Special	14508414
Coupling (female)	1	6.3	1/4"	Internal thread	1/4" NPT	1500	0.008	6	Special	14508415
Plug (male)	1	6.3	1/4"	Internal thread	1/4" BSP cyl.	1500	0.008	6	Special	14508416
Plug (male)	1	6.3	1/4"	Internal thread	1/4" NPT	1500	0.008	6	Special	14508417

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.