

STAUFF Push-to-connect coupling with poppet valve series HU



The HU series consists of a male tip designed according to ISO 7241-1 A and is compatible with female bodies of this type.

Characteristics

Series: HU

Material: Steel

Surface protection: Zinc-Nickel

Valve shape: Poppet valve

Minimum medium temperature (continuous): -25 °C

Maximum medium temperature (continuous): 100 °C

Standard: ISO 7241-1A

Connectable under residual pressure: Yes, with restrictions

Application

- Agricultural and forestry machinery

Technical Information

Connect under pressure:

- male tip up to the max. working pressure allowed

Type of component	Construction size	Nominal bore in DN mm	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Spillage ml	Max. flow rate l/min	Sealing	Article
Plug (male)	3	12.5	1/2"	Internal thread	1/2" NPT	250	2.7	100	NBR	14230143
Plug (male)	3	12.5	1/2"	Internal thread	3/4-16 UNF	250	2.7	100	NBR	14230144

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.