



ASCO Solenoid valve 2/2 Type: 32300 series 210 brass normally closed new

Characteristics

Series: 210
Type: 32300
Process connection: Internal thread (BSPP)
Function: Normally closed (NC)
Actuation: Pilot operated hung diaphragm
Minimum pressure difference: 0 bar
Maximum pressure difference: 16 bar
Electrical connection: Plug EN 175301-803 type A
Max. viscosity: 65 mm²/s
Housing material: Brass
Material coil housing: Epoxy
Material shorting ring: Copper
Working time: 100 %
Level of protection (IP value): IP65
Explosion-proof: No
SIL certified: No

Application

- In systems with a small differential pressure or as a drain from a pressureless tank. Neutral gases.
- Neutral liquids.
- Hydraulic oils.
- With FKM/FPM seals suitable for biofuels

Technical Information


- Robust construction.
- New design suitable for up to 16 bar.
- Response time 15 to 120 ms.

Options

- Emergency manual control version MO.
- Seals and membrane in EPDM or CR.
- Oxygen, oil and grease-free version.
- Other supply voltages.
- Explosion-proof versions.

Size table:

Type	Size	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Weight kg
210C493/494 AC	1/2"	86	51	30	70	45	58	112	0.9
210C493/494 DC	1/2"	91	56	33	70	50	58	107	1
210B454 AC/DC	1"	91	56	33	95	50	83	134	2
210D495 AC	3/4"	91	56	33	71	50	58	119	1
210D495 AC	3/4"	86	51	30	71	45	58	119	1
210D495 DC	3/4"	91	56	33	71	50	58	115	1.1
210C493/494 AC	3/8"	86	51	30	70	45	58	112	0.9
210C493/494 DC	3/8"	91	56	33	70	50	58	107	1



Size process connection	Orifice mm	Kvs value m ³ /h	Coil type	Supply voltage	Power	Starting power	Sealing	Membrane material	Medium temperature	Article
1/2" (15)	16	3.4	400425-101	24V AC	10.5 W / 23 VA	5 VA	NBR	NBR	From -20 °C to 85 °C	14535391

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Size process connection	Orifice mm	Kvs value m ³ /h	Coil type	Supply voltage	Power	Starting power	Sealing	Membrane material	Medium temperature	Article
1/2" [15]	16	3.4	400625-142	24V DC	12 W [hot] - 16.8 W [cold]		FPM	FPM	From -10 °C to 100 °C	14535415
1/2" [15]	16	3.4	400625-142	24V DC	12 W [hot] - 16.8 W [cold]		NBR	NBR	From -20 °C to 85 °C	14535413
1/2" [15]	16	3.4	400425-117	230V AC	10.5 W / 23 VA	5 VA	FPM	FPM	From -10 °C to 100 °C	14535414
1/2" [15]	16	3.4	400425-117	230V AC	10.5 W / 23 VA	5 VA	NBR	NBR	From -20 °C to 85 °C	14535392
1" [25]	25	9.6	400525-101	24V AC	15.4 W / 33.6 VA	110 VA	NBR	NBR	From -20 °C to 85 °C	14535423
1" [25]	25	9.6	400625-142	24V DC	12 W [hot] - 16.8 W [cold]		FPM	FPM	From -10 °C to 100 °C	14535422
1" [25]	25	9.6	400625-242	24V DC	16.8 W [hot] - 23 W [cold]		NBR	NBR	From -20 °C to 85 °C	14535424
1" [25]	25	9.6	400425-117	230V AC	15.4 W / 33.6 VA	110 VA	NBR	NBR	From -20 °C to 85 °C	14535421
3/4" [20]	19	4.7	400425-101	24V AC	10.5 W / 23 VA	5 VA	FPM	FPM	From -10 °C to 100 °C	14535420
3/4" [20]	19	4.7	400425-101	24V AC	10.5 W / 23 VA	5 VA	NBR	NBR	From -20 °C to 85 °C	14535416
3/4" [20]	19	4.7	400625-142	24V DC	12 W [hot] - 16.8 W [cold]		NBR	NBR	From -20 °C to 85 °C	14535418
3/4" [20]	19	4.7	400425-117	230V AC	10.5 W / 23 VA	5 VA	FPM	FPM	From -10 °C to 100 °C	14535419
3/4" [20]	19	4.7	400425-117	230V AC	10.5 W / 23 VA	5 VA	NBR	NBR	From -20 °C to 85 °C	14535417
3/8" [10]	16	2.6	400425-101	24V AC	10.5 W / 23 VA	5 VA	NBR	NBR	From -20 °C to 85 °C	14535388
3/8" [10]	16	2.6	400625-142	24V DC	12 W [hot] - 16.8 W [cold]		NBR	NBR	From -20 °C to 85 °C	14535390
3/8" [10]	16	2.6	400425-117	230V AC	10.5 W / 23 VA	5 VA	NBR	NBR	From -20 °C to 85 °C	14535389

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.