



ADCAPURE Check valve Series: SRTV10 Type: 8848V Stainless steel Tri-clamp ASME BPE

Characteristics

Series: SRTV10

Type: 8848V

Norm: ASME

Construction type: Vertical

Housing material: Stainless steel

Material quality: SS316L

Internal roughness value: Ra 0.51 µm

External roughness value: Ra 0.76 µm

Connection: Tri-clamp

With spring: Yes


Maximum medium temperature (continuous): 180 °C

Application

- Recommended in: Pharma

Size table:

DN	C mm	H mm	L mm	Weight kg
1/2" [15]	25	61	50	0.4
3/4" [20]	25	61	50	0.5
1" [25]	50.5	61	60	0.6
1.1/2" [40]	50.5	90	73	1.1
2" [50]	64	104	84	1.4
2.1/2" [65]	77.5	119	89	1.8
3" [80]	91	134	98	2.7
4" [100]	119	170	109	4.9



Nominal inner diameter	External tube diameter of connection	Standard connection	Pressure rating	Face to Face length	Valve shape	Sealing	Material disc	Spring material	Minimum medium temperature (continuous)	Article
	mm			mm					°C	
1/2" [15]	25	ASME-BPE	PN10	50	Flap	EPDM	1.4404	1.4401	-10	14543716
3/4" [20]	25	ASME-BPE	PN10	50	Flap	EPDM	1.4404	1.4401	-10	14543717
1" [25]	50.5	ASME-BPE	PN10	60	Flap	EPDM	1.4404	1.4401	-10	14543718
1.1/2" [40]	50.5	ASME-BPE	PN10	73	Flap	EPDM	1.4404	1.4401	-10	14543951
2" [50]	64	ASME-BPE	PN10	84	Flap	EPDM	1.4404	1.4401	-10	14543719
2.1/2" [65]	77.5	ASME-BPE	PN10	89	Flap	EPDM	1.4404	1.4401	-10	14543950
3" [80]	91	ASME-BPE	PN10	98	Flap	EPDM	1.4404	1.4401	-10	14543720
4" [100]	119	ASME-BPE	PN10	109	Flap	EPDM	1.4404	1.4401	-10	14543721

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.