

HYPRESS Hydraulic hose textile reinforced 3TE

Characteristics

Series: 3TE

Material of inner wall: Oil resistant synthetic rubber

Material of outer wall: Synthetic rubber, abrasion, weather and ozon resistant

Quality cover: Standard

Temperature range [°C]: -40 / 100 °C

EN standard: EN 854-3TE



Code	Hose ID (DN)	Hose ID in	Outer diameter mm	Maximum operating pressure bar	Minimum burst pressure bar	Minimum bending radius mm	Outside wall colour	Weight kg/m	Article
3TE-04	DN06	1/4"	14.4	145	580	45	Black	0.234	14573476
3TE-05	DN08	5/16"	16.9	130	520	55	Black	0.305	14573477
3TE-06	DN10	3/8"	18.5	110	440	70	Black	0.352	14573478
3TE-08	DN12	1/2"	21.7	93	372	85	Black	0.435	14573479
3TE-10	DN16	5/8"	25.9	80	320	105	Black	0.575	14573480
3TE-12	DN19	3/4"	29	70	280	130	Black	0.625	14573481
3TE-16	DN25	1"	35.9	55	220	150	Black	0.855	14573482

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.