

DANFOSS Quick coupling stainless steel H5000 series



Characteristics

Series: H5000

Material: Stainless steel 316L (1.4404)

Minimum medium temperature (continuous): -20 °C

Maximum medium temperature (continuous): 200 °C

Type of component	Coupling size (inch)	Connection type	Connection size	Maximum operating pressure bar	Max. flow rate l/min	Sealing	Article
Coupling (female)	3/8"	Internal thread	3/8" BSP cyl.	175	16.7	FKM	864854
Coupling (female)	1/2"	Internal thread	1/2" BSP cyl.	150	25.5	FKM	864919
Coupling (female)	3/4"	Internal thread	3/4" BSP cyl.	125	55	FKM	865095
Coupling (female)	1"	Internal thread	1" BSP cyl.	100	87	FKM	865133
Coupling (female)	1/4"	Internal thread	1/4" BSP cyl.	230	11.6	FKM	864838
Plug (male)	3/8"	Internal thread	3/8" BSP cyl.	175	16.7	FKM	864862
Plug (male)	1/2"	Internal thread	1/2" BSP cyl.	150	25.5	FKM	865060
Plug (male)	3/4"	Internal thread	3/4" BSP cyl.	125	55	FKM	773980
Plug (male)	1"	Internal thread	1" BSP cyl.	100	87	FKM	865141
Plug (male)	1/4"	Internal thread	1/4" BSP cyl.	230	11.6	FKM	864846

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.