



MHA ZENTGRAF 3-Way ball valve Series: 3KH Steel Cutting ring, heavy (S) PN315/400/500

Characteristics

Series: 3KH
Construction type: 3-way
Housing material: Steel
Surface protection: Zinc Plated
Connection: Cutting ring, heavy (S)
Standard connection: DIN 2353 / ISO 8434-1
Seat material: POM

Characteristics (2)

Spindle material: Steel
Minimum medium temperature (continuous): -20 °C
Maximum medium temperature (continuous): 100 °C

Nominal inner diameter	External tube diameter of connection	Connection, gland nut	Pressure rating	Face to Face norm	Manual operation	Ball bore	Secondary spindle seal material	Body seal	Weight	Article
	mm	mm							kg	
DN10	14	M 22x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	2.7	14613110
DN10	14	M 22x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	2.7	14613111
DN10	14	M 22x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	2.7	14613112
DN13	16	M 24x1.5	PN400	Manufacturer standard	Handle	L-bore	NBR	NBR	5.1	14613126
DN13	16	M 24x1.5	PN400	Manufacturer standard	Handle	T-bore	NBR	NBR	5.1	14613127
DN16	20	M 30x2	PN400	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	4.7	14613133
DN16	20	M 30x2	PN400	Manufacturer standard	Handle	L-bore	NBR	NBR	4.7	14613134
DN16	20	M 30x2	PN400	Manufacturer standard	Handle	T-bore	NBR	NBR	4.7	14613135
DN20	25	M 36x2	PN315	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	6.7	14613139
DN20	25	M 36x2	PN315	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	6.7	14613140
DN20	25	M 36x2	PN315	Manufacturer standard	Handle	L-bore	NBR	NBR	6.7	14613141
DN20	25	M 36x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	6.7	14613142
DN32/25	38	M 52x2	PN315	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	8.3	14613152
DN32/25	38	M 52x2	PN315	Manufacturer standard	Handle	T-bore	FPM (FKM)	FPM (FKM)	8.3	14613153
DN32/25	38	M 52x2	PN315	Manufacturer standard	Handle	L-bore	NBR	NBR	8.3	14613154
DN32/25	38	M 52x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	8.3	14613155
DN25	30	M 42x2	PN315	Manufacturer standard	Handle	L-bore	NBR	NBR	8.2	14613162
DN25	30	M 42x2	PN315	Manufacturer standard	Handle	T-bore	NBR	NBR	8.2	14613163
DN04	8	M 16x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	1.6	14613171
DN04	8	M 16x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	1.6	14613172
DN06	10	M 18x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	1.6	14613180
DN06	10	M 18x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	1.6	14613181
DN08	12	M 20x1.5	PN500	Manufacturer standard	Handle	L-bore	FPM (FKM)	FPM (FKM)	2.6	14613194
DN08	12	M 20x1.5	PN500	Manufacturer standard	Handle	L-bore	NBR	NBR	2.6	14613195
DN08	12	M 20x1.5	PN500	Manufacturer standard	Handle	T-bore	NBR	NBR	2.6	14613196

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.