

SKF Pillow Block Tapped Base Setscrew Locking Series P2BTSS

Characteristics

Series: P2BTSS

Housing style: Pillow Block Tapped Base

Bearing type: Ball bearing

Shaft Locking Type: Setscrew Locking

Application

• Recommended in: Food & Beverages

Basic series prefix P28 - Plummer block block (2 beld)	Bearing bore size Metric 20-204 digits unsated in men 20-204 digits unsated in men	Housing variant Equal to housing 3.1 socition	Bearing design C - NG (project ZPH unit) T + NNR Bearing additional features P + Gutter sealing schem and bearing without relabrication listiatures	
9281 - Short hase plummer block (2 bot) F28 - Out Branch (2 bot) F288 - 2-bot bracket fanged (2 bot) F48 - Spusre fanged (6 bot) WSTU - Take-up (Wide stat)	lends: 2xt digit: number of whole inches. 2xd-3xd sideenth of an inch	Z = Housing with inch threaded holes for metric shaft slars bearings		
XXX(X) X(X)	xxx x -	х х	х х	_ xx
Housing material C + Composite for food and between	Bearing bore size modifier L - Bearing and housing of the normal (and unit)	Bearing mater 55 - Stainless steel inner rings, and grub sor- ers with stainless is food-compatible ry	r ring and outer ows; seals and fing- sed inserts and	Variant BFW - Unit with back seel and end cover mounted

Manufacturer ID	Housing material	Bearing material	Shaft diameter	Article
			mm	
P2BTSS 25M-YTPSS	Stainless steel	Stainless steel	25	13501386
P2BTSS 30M-YTPSS	Stainless steel	Stainless steel	30	13501387

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR1619920320114857_EN_17.05.2024