


Hose coupling type SHM HYDR with male thread in steel for ferrule assembly



Characteristics

Type of component: Hose tail coupling

Material: Steel

Connection type: Threaded coupling

Hose fitting type: Male thread

Connection termination: NPT

Elbow angle [degr.]: 0 °

Hose tail execution: Serrated, with safety collar

Temperature range [°C]: -40 / 260 °C

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
1/4"	DN06	315	4568	11180772
3/8"	DN10	315	4568	11180794
1/2"	DN12	315	4568	11173489
3/8"	DN12	315	4568	11354244
3/4"	DN19	160	2320	11173536
1"	DN25	160	2320	11173537
1.1/4"	DN32	160	2320	11180795
1.1/2"	DN38	160	2320	11180797
2"	DN50	100	1450	11180799
1/2"	DN12	315	4568	11213704
3/4"	DN19	160	2320	11213705
1"	DN25	160	2320	11213706
1.1/2"	DN38	160	2320	11213708
2"	DN50	100	1450	11213709

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.