



WEG 3 Phase motor W22Xdb Cast Iron B3T (6p)

Flameproof motors designed to meet the latest market requirements and certifications for Hazardous Areas. Offer high efficiency, low noise and vibration levels and allow applications in severe duties.

Characteristics

Series: W22Xdb

Type: B3T

Speed: 1000 rpm

Mounting: B3T

Number of poles: 6

Full load speed: 985 rpm

Full load torque: 7.701 Nm

Nominal rated frequency: 50 Hz

Material: Cast iron

PTC thermistor: Yes

Energy efficiency class	Power kW	ATEX Zone	Nominal rated voltage V	Frame size acc. to IEC	Article
IE2	0.18	Zone 1	230/400	71	13022801
IE2	0.25	Zone 1	230/400	71	13022826
IE2	0.37	Zone 1	230/400	80	13022831
IE2	0.55	Zone 1	230/400	80	13022836
IE3	0.18	Zone 1	230/400	71	13192385
IE3	0.25	Zone 1	230/400	71	13192390
IE3	0.37	Zone 1	230/400	80	13192396
IE3	0.55	Zone 1	230/400	80	13192401
IE3	0.75	Zone 1	230/400	90S/L	13192406
IE3	1.1	Zone 1	230/400	100L	13192412
IE3	1.5	Zone 1	230/400	100L	13192417
IE3	2.2	Zone 1	400/690	112M	13192422
IE3	3	Zone 1	400/690	132S/M	13192428
IE3	4	Zone 1	400/690	132S/M	13192433
IE3	5.5	Zone 1	400/690	132S/M	13192438
IE3	7.5	Zone 1	400/690	160M/L	13192441
IE3	9.2	Zone 1	400/690	160M/L	13192444
IE3	11	Zone 1	400/690	160M/L	13192447
IE3	15	Zone 1	400/690	180M/L	13192450
IE3	18.5	Zone 1	400/690	200M/L	13192453
IE3	22	Zone 1	400/690	200M/L	13192456
IE3	30	Zone 1	400/690	225S/M	13192459
IE3	37	Zone 1	400/690	250S/M	13192462

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.