



WEG 3 Phase motor W22 Cast iron B3T (2P)

Characteristics

Series: W22
Type: B3T
Speed: 3000 rpm
Mounting: B3T
Number of poles: 2
Full load speed: 2720 rpm
Full load torque: 0.411 Nm
Nominal rated frequency: 50 Hz
Material: Cast iron
PTC thermistor: Yes

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Article
IE2	0.12	230/400	63	11	12318221
IE2	0.18	230/400	63	11	12318224
IE2	0.25	230/400	63	11	12318227
IE2	0.25	290/500	63		12767262
IE2	0.37	230/400	63	11	13025077
IE2	0.37	230/400	71	14	12318230
IE2	0.55	230/400	71	14	12318233
IE2	0.55	290/500	71		12767263
IE3	0.12	230/400	63	11	12686998
IE3	0.12	230/400	63	11	12687574
IE3	0.18	230/400	63	11	12687005
IE3	0.18	230/400	63	11	12687577
IE3	0.25	230/400	63	11	12687011
IE3	0.25	230/400	63	11	12687580
IE3	0.37	230/400	71	14	12687016
IE3	0.37	230/400	71	14	12687583
IE3	0.55	230/400	71	14	12687022
IE3	0.55	230/400	71	14	12687586
IE3	0.75	230/400	71		13608948
IE3	0.75	230/400	80	19	12687027
IE3	0.75	230/400	80	19	12687589
IE3	1.1	230/400	80	19	12687032
IE3	1.1	230/400	80	19	12687592
IE3	1.5	230/400	90S	24	12687049
IE3	1.5	230/400	90S	24	12687595
IE3	1.5	230/400	L80		13608949
IE3	2.2	230/400	90L	24	12687054
IE3	2.2	230/400	90L	24	12687598
IE3	2.2	400/690	90L	24	12695043
IE3	2.2	400/690	90L	24	13190803
IE3	3	230/400	100L	28	12687059
IE3	3	230/400	100L	28	12687601
IE3	3	400/690	100L	28	12695049
IE3	3	400/690	100L	28	12657953
IE3	4	230/400	100L		13608963
IE3	4	230/400	112M	28	13402681
IE3	4	230/400	112M	28	13402682

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Article
IE3	4	400/690	112M	28	12687065
IE3	4	400/690	112M	28	12687604
IE3	5.5	230/400	132S	38	13402715
IE3	5.5	230/400	132S	38	13402716
IE3	5.5	400/690	132S	38	12687070
IE3	5.5	400/690	132S	38	12687760
IE3	5.5	400/690	L112M		13608964
IE3	7.5	230/400	132S	38	13402747
IE3	7.5	230/400	132S	38	13402748
IE3	7.5	400/690	132S	38	12687075
IE3	7.5	400/690	132S	38	12687609
IE3	9.2	230/400	132M	38	13402774
IE3	9.2	230/400	132M	38	13402775
IE3	9.2	400/690	132M	38	12687080
IE3	9.2	400/690	132M	38	12687762
IE3	11	230/400	132M		13608968
IE3	11	230/400	160M	42	13402795
IE3	11	400/690	132M		13608969
IE3	11	400/690	132M	38	13025210
IE3	11	400/690	160M	42	12687085
IE3	15	230/400	160M	42	13402807
IE3	15	400/690	160M	42	12687702
IE3	18.5	230/400	160L	42	13402819
IE3	18.5	400/690	160L	42	12687088
IE3	22	230/400	180M	48	13402831
IE3	22	400/690	132M		13632474
IE3	22	400/690	160L		14248079
IE3	22	400/690	180M	48	12687090
IE3	30	230/400	200L	55	13402843
IE3	30	400/690	180L	48	12696969
IE3	30	400/690	200L	55	12687092
IE3	37	230/400	200L	55	13402856
IE3	37	400/690	200L	55	12687094
IE3	45	230/400	225S/M		12763883
IE3	45	230/400	225S/M	55	13402869
IE3	45	400/690	225S/M	55	12687097
IE3	55	230/400	250S/M	60	13402881
IE3	55	400/690	250S/M	60	12687100
IE3	75	400/690	280S/M	65	12687103
IE3	90	400/690	280S/M	65	12687106
IE3	110	400/690	315S/M	65	12687109
IE3	132	400/690	315S/M	65	12687112
IE3	200	400/690	315L	65	12687121
IE3	220	400/690	315L	65	12687124
IE3	250	400/690	315L	65	12687127
IE3	260	400/690	315L	65	12687130
IE3	280	400/690	315L	65	12687133
IE3	315	400/690	355M/L	75	12687137
IE3	330	400/690	355M/L	75	12728980
IE3	355	400/690	355M/L		12763961
IE3	370	400/690	355A/B	75	12728993
IE3	400	400/690	355A/B	75	12728996
IE3	450	400/690	355A/B	75	12728999

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Article
IE4	0.25	230/400	63	11	13310895
IE4	0.25	230/400	63	11	13308688
IE4	0.37	230/400	71	14	13310900
IE4	0.37	230/400	71	14	13308693
IE4	0.55	230/400	80	19	13310905
IE4	0.55	230/400	80	19	13308698
IE4	0.75	230/400	80	19	13310911
IE4	0.75	230/400	80	19	13308703
IE4	1.1	230/400	90S	24	13310916
IE4	1.1	230/400	90S	24	13308708
IE4	1.5	230/400	90L	24	13310921
IE4	1.5	230/400	90L	24	13308713
IE4	2.2	230/400	100L	28	13310926
IE4	2.2	230/400	100L	28	13308718
IE4	2.2	400/690	100L	28	13403638
IE4	2.2	400/690	100L	28	13403639
IE4	3	230/400	L100L	28	13310931
IE4	3	230/400	L100L	28	13308723
IE4	3	400/690	L100L	28	13310936
IE4	3	400/690	L100L	28	13308728
IE4	4	230/400	L112M		13597082
IE4	4	230/400	L112M		14156092
IE4	4	400/690	L112M	28	13310941
IE4	4	400/690	L112M	28	13308733
IE4	5.5	400/690	132S	38	12616200
IE4	5.5	400/690	132S	38	13194257
IE4	7.5	400/690	132S	38	12616205
IE4	7.5	400/690	132S	38	13194273
IE4	9.2	400/690	L132M/L	38	12616210
IE4	9.2	400/690	L132M/L	38	13194283
IE4	11	400/690	160M	42	12616215
IE4	15	400/690	160M	42	12616218
IE4	18.5	400/690	160L	42	12616221
IE4	22	400/690	180M	48	12616224
IE4	30	400/690	200L	55	12616227
IE4	37	400/690	200L	55	12616230
IE4	45	400/690	225S/M	55	12616233
IE4	55	400/690	250S/M	60	12616236
IE4	75	400/690	280S/M	65	12616239
IE4	90	400/690	280S/M	65	12616242
IE4	110	400/690	315S/M	65	12616245
IE4	132	400/690	315S/M	65	12616248
IE4	150	400/690	315S/M	65	12616251
IE4	160	400/690	315S/M	65	12616254
IE4	185	400/690	315L	65	12616257
IE4	200	400/690	315L	65	12616260
IE4	220	400/690	315L	65	12616263
IE4	250	400/690	315L	65	12616266
IE4	260	400/690	315L	65	12616269
IE4	280	400/690	315L	75	12616272
IE4	300	400/690	355M/L	75	12616275
IE4	315	400/690	355M/L	75	12616278
IE4	330	400/690	355A/B	75	12616281

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Energy efficiency class	Power kW	Nominal rated voltage V	Frame size acc. to IEC	Shaft diameter mm	Article
IE4	355	400/690	355A/B	75	12616283

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.