



HONEYWELL Pressure reducing valve Type 11190 series D06FN brass external thread



Characteristics

Series: D06FN-B

Type: 11190

Model: Direct-acting

Connection: External thread (BSPP)

Maximum inlet pressure: 25 bar

Medium temperature: 0 / 60 °C

Housing material: Brass

Material disc: Synthetic material

Seat material: Synthetic material

Membrane material: NBR

Spring material: Spring steel

Material spring bonnet: Synthetic material

Filter element material: Stainless steel

With couplers: Yes

Backflow preventer: No

Application

- Water.
- General industry.

Technical Information

- Fitted with screening element.
- Balanced valve.
- Three-piece coupling with BSPP outer wire.

Nominal inner diameter	Capacity type	Kvs value m³/h	Reduced pressure range bar	Article
1/2" [15]	Standard	2.4	0.5 / 2	10051468
3/4" [20]	Standard	3.1	0.5 / 2	10051469
1" [25]	Standard	7.6	0.5 / 2	10051466
1.1/4" [32]	Standard	9.1	0.5 / 2	10051471
1.1/2" [40]	Standard	12.6	0.5 / 2	10051470
2" [50]	Standard	12	0.5 / 2	10051467

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.