



GF Ball check valve Series: 561 PVC-U Glued end PN16

Characteristics

Series: 561

Construction type: Straight

Housing material: PVC-U

Connection: Glued end

External tube diameter of connection mm	Pressure rating	Valve shape	Sealing	Minimum medium temperature [continuous] °C	Maximum medium temperature [continuous] °C	Article
16	PN16	Ball	EPDM	0	60	12301774
16	PN16	Ball	FPM (FKM)	0	60	12301779
20	PN16	Ball	EPDM	0	60	12301775
20	PN16	Ball	FPM (FKM)	0	60	12301780
25	PN16	Ball	EPDM	0	60	12301776
25	PN16	Ball	FPM (FKM)	0	60	12301781
32	PN16	Ball	EPDM	0	60	12262323
32	PN16	Ball	FPM (FKM)	0	60	12301782
40	PN16	Ball	FPM (FKM)	0	60	12301793
50	PN16	Ball	EPDM	0	60	12301777
50	PN16	Ball	FPM (FKM)	0	60	12301794
63	PN16	Ball	EPDM	0	60	12301778
63	PN16	Ball	FPM (FKM)	0	60	12301795
75	PN16	Ball	EPDM	0	60	12336743
75	PN16	Ball	FPM (FKM)	0	60	12336745
90	PN16	Ball	EPDM	0	60	12301687
90	PN16	Ball	FPM (FKM)	0	60	12301688
110	PN16	Ball	EPDM	0	60	12336744
110	PN16	Ball	FPM (FKM)	0	60	12336746

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.