



GF Ball check valve Series: 561 PVC-U Flange PN16

Characteristics

Series: 561

Construction type: Straight

Housing material: PVC-U

Connection: Flange

Nominal inner diameter	External tube diameter of connection	Pressure rating	Valve shape	Sealing	Minimum medium temperature [continuous]	Maximum medium temperature [continuous]	Article
	mm				°C	°C	
DN15	20	PN16	Ball	EPDM	0	60	12336747
DN15	20	PN16	Ball	FPM (FKM)	0	60	12301712
DN20	25	PN16	Ball	EPDM	0	60	12301709
DN25	32	PN16	Ball	EPDM	0	60	12301710
DN25	32	PN16	Ball	FPM (FKM)	0	60	12301713
DN32	40	PN16	Ball	EPDM	0	60	12336748
DN40	50	PN16	Ball	EPDM	0	60	12336749
DN40	50	PN16	Ball	FPM (FKM)	0	60	12301714
DN50	63	PN16	Ball	EPDM	0	60	12301711
DN50	63	PN16	Ball	FPM (FKM)	0	60	11023259

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.