

KEMPER Regulating valve Series: 141 OG Type: 2419K Dynamic Bronze KIWA External thread (BSPP)

bronze regulating- or commissioning valve with threaded connection in PN25.




Area of application

- Heating and cooling systems.
- Industrial applications.
- Installation technique.

Details

- Adjustable Kv values.
- With measuring nipples.
- Oventrop Hydrocontrol VTR.
- Pressure difference and capacity can be measured by a measurement computer.
- Only fig. 2612 has a fill/drain connection.



Characteristics

Series: 141 OG

Type: 2419K

Housing material: Bronze

Material quality: CuSn5Zn5Pb2

Connection: External thread (BSPP)

Type of control gear: Dynamic

Thermostatic: Yes

Application: Tap water

With measuring nipples: Yes

Maximum medium temperature (continuous): 90 °C

KIWA: Yes

With position indicator: Yes

Application

- Recommended in: Utilities

Nominal inner diameter	Pressure rating	Adjustment range °C	Control range l/h	Kvs value m³/h	Kv value m³/h	Article
DN15	PN16	50 / 65	100 / 1080	1.08	0.1 / 1.08	11815395
DN20	PN16	50 / 65	200 / 1940	1.94	0.2 / 1.94	11815396
DN25	PN16	50 / 65	410 / 2480	2.48	0.41 / 2.48	11815397

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.