



ASCO Dust collector pulse valve 2/2 Type: 32231 series 353 aluminium

Characteristics

Series: 353

Type: 32231

Function: Normally closed (NC)

Actuation: Indirect-acting


Electrical connection: Plug EN 175301-803 type A

Housing material: Aluminium

Sealing: CR

Working time: 100 %

Level of protection (IP value): IP65



Size process connection	Process connection	Orifice mm	Kvs value m³/h	Minimum pressure difference bar	Coil type	Supply voltage	Power	Medium temperature	Ambient temperature	Article
1.1/2" (40)	Internal thread (BSPP)	52	46	0.35	SPC 35030	24V DC	22 W	From -20 °C to 85 °C	From -20 to 85 °C	12212211
1.1/2" (40)	Internal thread (BSPP)	52	46	0.35	SPC 35032	230V AC	6,3 W	From -20 °C to 85 °C	From -20 to 85 °C	11602337
2.1/2" (65)	Internal thread (BSPP)	66				24V DC				11657649

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.