



ASECOS Fire protection cabinet with 2 wing doors, 1947x1164x620 mm



Safety cabinet Q30, RAL 1004

- **Sturdy design in cabinet widths 564, 864 and 1164 mm**

Body:

fire resistant, melamine resin coated special plates in the colour anthracite grey (similar RAL 7016)

Doors:

Made of steel sheeting with structure - powder-coated and optional with large glass window made of fire protection glass EI 30 according to DIN EN 13501-2. Components relating to safety are located outside of the cabinet interior

- **Easy to operate**

Smooth-operating doors, adjustable in any opening position
In the event of fire open doors close independently if open
Door lockable with profile half cylinder
With integrated ventilation and exhaust system for connection NW 75mm) to technical exhaust

- **Interior furnishing**

Standard with 3 height-adjustable shelves (raster 32 mm)
Load capacity 75 kg (evenly spread), floor catchment pan according to StawaR with perforated steel insert as first storage level

- **Easy transport**

Integrated transport base for easy internal transport
Base panel available upon enquiry

- **Fire resistance 30 minutes**

Type 30 safety cabinet for storage of flammable liquids in work rooms according to DIN EN 14470-1 and TRGS 510.
GS certified, CE-conform

Door RAL 1004

Width mm	Depth mm	Height mm	Article
1164	620	1947	12974957
1164	620	1947	12974955
1164	620	1947	12974959
1164	620	1947	12974954

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.