

## Acrylic traffic mirror, standard version with white/red reflectors



Traffic mirror



## Optimal view - on the road and company premises

the red reflectors (Type RA2) reduce the risk of accidents especially in bad weather and darkness.

Robust design

acrylic according to DIN ISO 179-1, approx. 70

% more impact resistant than glass, UV-resistant and wind load tested up to wind force 12. The anti-fog versions also feature a special coating.

## Scope of delivery

solid 4-point ball joint mount for accurate fastening. Wall or pipe posts (Ø 50-85

\* Recommended guide values

| Width | Height | Sight distance | Weight | Article  |
|-------|--------|----------------|--------|----------|
| mm    | mm     | m              | kg     |          |
| 600   | 400    | 9–15           | 10     | 12971017 |
| 800   | 600    | 15–22          | 15     | 12970999 |
| 1000  | 800    | 22–27          | 21     | 12971012 |
|       |        | 15-22          | 11     | 12971019 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR2277168451983477\_EN\_05.05.2024