



FENNER V-pulley for taper bush section SPB - 4 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: B/SPB/QXPB

Number of grooves: 4

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
29	25	29
18.5	45	18.5
15.5	51	15.5
16	51	16
9	65	9
3.5	65	3.5
8.5	65	8.5
3	76	3

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
112	2012	3	Cast iron	16.1	29	25	29	11422028
118	1610	3	Cast iron	16.1	29	25	29	11422034
125	2012		Cast iron	16.1				11422038
132	2012		Cast iron	16.1				11422044
140	2517		Cast iron	16.1				11422049
150	2517		Cast iron	16.1				11422055
160	2517		Cast iron	16.1				11422062
170	2517	3	Cast iron	16.1	18.5	45	18.5	11422070
180	2517		Cast iron	16.1				11422077
190	2517		Cast iron	16.1				11422085
200	3020		Cast iron	16.1				11422093
224	3020	3	Cast iron	16.1	15.5	51	15.5	11422107
236	3020		Cast iron	16.1				11422115
250	3020		Cast iron	16.1				11422122
265	3020	7	Cast iron	16.1	16	51	16	11422348
300	3525	7	Cast iron	16.1	9	65	9	11422137
315	3525	7	Cast iron	16.1	3.5	65	3.5	11422143
315	3535		Cast iron	16.1				856533
335	3525	7	Cast iron	16.1	9	65	9	11422150
335	3525		Cast iron	16.1				23835980

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Pitch circle diameter mm	Taper Lock	Model	Material	Groove width mm	K mm	L mm	M mm	Article
400	3525	4	Cast iron	16.1	8.5	65	8.5	11422164
500	3525		Cast iron	16.1				11422184
630	3525	4	Cast iron	16.1	8.5	65	8.5	11422198
710	3525		Cast iron	16.1				11457806
900	4030	5	Cast iron	16.1	3	76	3	11422211
1000	4030	4	Cast iron	16.1	3	76	3	11422215

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.