



FENNER V-pulley for taper bush section SPB - 6 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: B/SPB/QXPB

Number of grooves: 6

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
34.5	51	34.5
28	65	28
27.5	65	27.5
16	89	16
15.5	89	15.5
9	102	9

Pitch circle diameter mm	Taper Lock	Model	Material	Groove width mm	K mm	L mm	M mm	Article
140	2517		Cast iron	16.1				11422051
150	2517		Cast iron	16.1				11422058
160	3020		Cast iron	16.1				11422064
170	3020		Cast iron	16.1				11422072
180	3020		Cast iron	16.1				11422079
200	3020	3	Cast iron	16.1	34.5	51	34.5	11422095
224	3525	3	Cast iron	16.1	28	65	28	11422110
250	3525	3	Cast iron	16.1	28	65	28	11422124
280	3525	7	Cast iron	16.1	27.5	65	27.5	11422132
300	3525	7	Cast iron	16.1	28	65	28	11422139
315	3525	7	Cast iron	16.1	27.5	65	27.5	11422145
335	3525		Cast iron	16.1				11422152
355	3525	5	Cast iron	16.1	27.5	65	27.5	11422159
400	3525	5	Cast iron	16.1	27.5	65	27.5	11422166
450	3525	5	Cast iron	16.1	27.5	65	27.5	11422180
500	3525	5	Cast iron	16.1	27.5	65	27.5	11422186
560	3525	5	Cast iron	16.1	27.5	65	27.5	11422192
630	3525	5	Cast iron	16.1	27.5	65	27.5	11422200
710	4535	5	Cast iron	16.1	16	89	16	11459827
800	4535	5	Cast iron	16.1	15.5	89	15.5	11422208
900	4545		Cast iron	16.1				11422212
1000	4535		Cast iron	16.1				11422218
1250	5040	5	Cast iron	16.1	9	102	9	11422225

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.