



FENNER V-pulley for taper bush section SPC - 6 grooves

Fenner® Taper Lock® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: C/SPC/QXPC

Number of grooves: 6

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
48.5	65	48.5
36.5	89	36.5
30	102	30

Pitch circle diameter mm	Taper Lock	Model	Material	Groove width mm	K mm	L mm	M mm	Article
212	3525	3	Cast iron	22	48.5	65	48.5	11422237
250	3525	3	Cast iron	22	48.5	65	48.5	11422250
280	3525	3	Cast iron	22	48.5	65	48.5	11422261
300	3525	7	Cast iron	22	48.5	65	48.5	11422267
315	3525	7	Cast iron	22	48.5	65	48.5	11422271
355	3525	7	Cast iron	22	48.5	65	48.5	11422281
375	3525	7	Cast iron	22	48.5	65	48.5	11422287
400	3525	7	Cast iron	22	48.5	65	48.5	11422293
425	4535	7	Cast iron	22	36.5	89	36.5	11422299
450	4535	7	Cast iron	22	36.5	89	36.5	11422304
475	4535	7	Cast iron	22	36.5	89	36.5	11422311
500	4535	5	Cast iron	22	36.5	89	36.5	11422314
500	4545		Cast iron	22				11444271
530	4535	5	Cast iron	22	36.5	89	36.5	11422318
630	4535	5	Cast iron	22	36.5	89	36.5	11422327
710	5040	5	Cast iron	22	30	102	30	11422330
1000	5040	5	Cast iron	22	30	102	30	11422335
1250	5040	5	Cast iron	22	30	102	30	11422339

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.