



FENNER V-pulley for taper bush section SPC - 8 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: C/SPC/QXPC

Number of grooves: 8

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
74	65	74
68.5	76	68.5
62	89	62
55.5	102	55.5

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
200	3525	3	Cast iron	22	74	65	74	11422232
224	3525	3	Cast iron	22	74	65	74	11422242
250	3525	3	Cast iron	22	74	65	74	11422251
265	3525	3	Cast iron	22	74	65	74	11422256
280	3525	3	Cast iron	22	74	65	74	11422262
300	3525	7	Cast iron	22	74	65	74	11422268
315	3525	7	Cast iron	22	74	65	74	11422272
335	3525	7	Cast iron	22	74	65	74	11422277
355	3525		Cast iron	22				11422283
375	4030	7	Cast iron	22	68.5	76	68.5	11422288
400	4030	7	Cast iron	22	68.5	76	68.5	11422294
400	4545		Cast iron	22				853917
425	4535	7	Cast iron	22	62	89	62	11422300
450	4535	7	Cast iron	22	62	89	62	11422305
500	4535	7	Cast iron	22	62	89	62	11422315
530	4535	7	Cast iron	22	62	89	62	11422319
560	4535	5	Cast iron	22	62	89	62	11422322
560	4535		Cast iron	22				23836131
630	4535	5	Cast iron	22	62	89	62	11422328
800	5040	5	Cast iron	22	55.5	102	55.5	11422334
1000	5040	5	Cast iron	22	55.5	102	55.5	11422336

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.