


DANFOSS Pressure relief valve 2-1

Characteristics

Version: Screw in cartridge valves

Type of valve: Direct



Cavity	Cavity mm	Max. operating pressure bar	Max. oilflow l/min	Adjustment range	Article
C-8-2	350	30	3,4 - 100 bar		12155343
C-8-2	350	30	70 - 210 bar		1049469
C-8-2	350	30	70 - 350 bar		12155344
C-10-2	250	76	3,5 - 20 bar		12155346
C-10-2	250	76	7 - 41 bar		12155347
C-10-2	250	76	14 - 62 bar		12155348
C-10-2	250	76	20 - 124 bar		12155349
C-10-2	250	76	41 - 250 bar		12155350
C-10-2	350	76	7 - 86 bar		12155345
C-10-2	350	76	17 - 175 bar		1049438
C-10-2	350	76	38 - 350 bar		1049440
C-8-2	350	30	3,4 - 100 bar		1034270
C-10-2	250	76	41 - 250 bar		1049287
C-10-2	350	76	7 - 86 bar		1034274
C-10-2	350	76	17 - 175 bar		1034275
C-10-2	350	76	38 - 350 bar		1034276
C-16-2	350	303	35 - 90 bar		1034281
C-8-2	350	30	3,4 - 100 bar		1049471
C-8-2	350	30	70 - 210 bar		1049473
C-8-2	350	30	70 - 210 bar		1049472
C-10-2	350	76	3,45 - 30 bar		1034277
C-10-2	350	76	7 - 86 bar		1034278
C-10-2	350	76	17 - 175 bar		1034279
C-10-2	350	76	38 - 350 bar		1034280
C-16-2	350	303	35 - 90 bar		1034284
C-16-2	350	303	83 - 240 bar		1034285
C-16-2	350	303	140 - 350 bar		1034286

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.