


DANFOSS Pressure relief valve P-T



Characteristics

Version: Sandwich

Size: NG6/Cetop 3

Type of valve: From P to T

Material: Steel

Plug type: VSTIR1/4ED



Model	Max. operating pressure bar	Max. oilflow l/min	Adjustment range	Cartridge model	Manifold type	Height	Gauge port	Article
Conventional	250	60	7 - 140 bar	RV5 10 C 0 20	A321P	43,2		12218208
Conventional	250	60	17 - 240 bar	RV5 10 C 0 35	A321P	43,2		12218209
Conventional	315	60	3 - 100 bar			40	No	1034080
Conventional	315	60	3 - 50 bar			40	No	1041169
Conventional	315	60	10 - 200 bar			40	No	1034081
Conventional	315	60	10 - 200 bar			40	1/4" BSP	1041182
Conventional	315	60	50 - 315 bar			40	No	1041188
Conventional	315	60	50 - 315 bar			40	1/4" BSP	1033753
Conventional	315	120	4 - 100 bar			50	1/8" BSP	1048587
Conventional	315	120	4 - 200 bar			50	1/8" BSP	1048588
Conventional	315	120	4 - 315 bar			50	1/8" BSP	1033730
Conventional	315	120	4 - 50 bar			50	1/8" BSP	1048584

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.