



ASCO Solenoid valve 3/2 fig. 33210 series 320 brass

Characteristics

Series: 320
Type: 33210
Model: Solenoid valve three way
Connection air exhaust(s): 1/4" [8]
Function: Normally closed [NC]
Actuation: Direct-acting
Electrical connection: Plug EN 175301-803 type A
Including plug: Yes
Max. viscosity: 65 mm²/s
Minimum pressure difference: 0 bar
Housing material: Brass
Sealing: NBR
Material coil housing: Epoxy

Characteristics [2]

Material shorting ring: Copper
Working time: 100 %
Level of protection (IP value): IP65
Emergency manual operation: No
Explosion-proof: No
SIL certified: No
Medium temperature: From -20 °C to 90 °C
Ambient temperature: From -20 °C to 75 °C

Process connection	Size process connection	Coil type	Supply voltage	Frequency	Power	Starting power	Orifice mm	Kvs value m ³ /h	Maximum pressure difference bar	Article
Internal thread (NPT)	1/4" [8]	400425-101	24V AC	50Hz	10.5 W / 23 VA	55 VA	2.4	0.1	10	11489173
Internal thread (NPT)	1/4" [8]	400425-101	24V AC	50Hz	10.5 W / 23 VA	55 VA	3.2	0.21	6	11489176
Internal thread (NPT)	1/4" [8]	SPC 400425-142	24V DC		9 W (hot) - 11.2 W (cold)		1.6	0.08	11	12160035
Internal thread (NPT)	1/4" [8]	SPC 400425-142	24V DC		9 W (hot) - 11.2 W (cold)		2.4	0.1	8	11489174
Internal thread (NPT)	1/4" [8]	SPC 400425-142	24V DC		9 W (hot) - 11.2 W (cold)		3.2	0.21	4	11489177
Internal thread (NPT)	1/4" [8]	400425-118	115V AC	50Hz	10.5 W / 23 VA	55 VA	2.4	0.1	10	13407102
Internal thread (NPT)	1/4" [8]	400425-117	230V AC	50Hz	10.5 W / 23 VA	55 VA	2.4	0.1	10	11277640
Internal thread (NPT)	1/4" [8]	400425-117	230V AC	50Hz	10.5 W / 23 VA	55 VA	3.2	0.21	6	11489175
Internal thread (NPT)	1/4" [8]	400425-117	230V AC	50Hz	10.5 W / 23 VA	55 VA	4.4	0.3	3	13407099
Internal thread (NPT)	1/4" [8]	400425-217	230V AC	50Hz	16.7 W / 35VA	78 VA	1.6	0.08	15	11612776

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.