



ASCO Solenoid valve 3/2 fig. 33211 series 320 brass

Characteristics

Series: 320
Type: 33211
Model: Solenoid valve three way
Function: Normally open (NO)
Actuation: Direct-acting
Including plug: Yes
Orifice: 2.4 mm
Kvs value: 0.21 m³/h
Max. viscosity: 65 mm²/s
Minimum pressure difference: 0 bar
Housing material: Brass
Sealing: NBR
Material coil housing: Epoxy
Material shorting ring: Copper

Characteristics [2]

Working time: 100 %
Level of protection (IP value): IP65
Emergency manual operation: No
Explosion-proof: No
SIL certified: No
Medium temperature: From -20 °C to 90 °C
Ambient temperature: From -20 °C to 75 °C

Process connection	Size process connection	Connection air exhaust(s)	Coil type	Supply voltage	Frequency	Electrical connection	Power	Starting power	Maximum pressure difference bar	Article
Internal thread (NPT)	1/4" [8]	1/4" [8]	400425-101	24V AC	50Hz	Plug EN 175301-803 type A	10.5 W / 23 VA	55 VA	10	11489179
Internal thread (NPT)	1/4" [8]	1/4" [8]	SPC 400425-142	24V DC		Plug EN 175301-803 type A	9 W (hot) - 11.2 W (cold)		7	11489180
Internal thread (NPT)	1/4" [8]	1/4" [8]	400425-117	230V AC	50Hz	Plug EN 175301-803 type A	10.5 W / 23 VA	55 VA	10	11489178

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.