

CONTARINI DA Cylinder HM0PM



Characteristics

Type: HM0PM

Type (DA/SA): Double acting

Max. operating pressure: 350 bar

Front fixation: None

Rear fixation: None

Bore mm	Number of extensions	Outer diameter piston rod mm	Stroke mm	Built-in size mm	Oilports	Article
60	1	40	200	350	3/8" BSP	12953352
60	1	40	400	550	3/8" BSP	12953353
60	1	40	600	750	3/8" BSP	12953354
60	1	40	800	950	3/8" BSP	12953355
60	1	40	1000	1,150	3/8" BSP	12953356
70	1	40	200	375	3/8" BSP	12953357
70	1	40	400	575	3/8" BSP	12953358
70	1	40	600	775	3/8" BSP	12953359
70	1	40	800	975	3/8" BSP	12953360
70	1	40	1000	1,175	3/8" BSP	12953361
80	1	50	200	395	BSP female 1/2" BSP	12953362
80	1	50	400	595	BSP female 1/2" BSP	12953363
80	1	50	600	795	BSP female 1/2" BSP	12953364
80	1	50	800	995	BSP female 1/2" BSP	12953365
80	1	50	1000	1,195	BSP female 1/2" BSP	12953366
90	1	60	200	400	BSP female 1/2" BSP	12953367
90	1	60	400	600	BSP female 1/2" BSP	12953368
90	1	60	600	800	BSP female 1/2" BSP	12953369
90	1	60	800	1,000	BSP female 1/2" BSP	12953370
90	1	60	1000	1,200	BSP female 1/2" BSP	12953371
100	1	60	200	405	BSP female 1/2" BSP	12953372
100	1	60	400	605	BSP female 1/2" BSP	12953374
100	1	60	600	805	BSP female 1/2" BSP	12953375
100	1	60	800	1,005	BSP female 1/2" BSP	12953376
100	1	60	1000	1,205	BSP female 1/2" BSP	12953377
120	1	70	200	435	BSP female 1/2" BSP	12953378
120	1	70	400	635	BSP female 1/2" BSP	12953379
120	1	70	600	835	BSP female 1/2" BSP	12953380
120	1	70	800	1,035	BSP female 1/2" BSP	12953381
120	1	70	1000	1,235	BSP female 1/2" BSP	12953382

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.