

AKO Pinch valve Series: VMC-R Type: 210R Pneumatic operated Weld end DIN 11850 row 2



Characteristics

Series: VMC-R

Type: 210R

Norm: EN (DIN)

Housing material: Stainless steel

Material quality: AISi10Mg

Connection: Welded end

Standard welding connection: DIN 11850 row 2


Operation: Pneumatic operated

Minimum medium temperature [continuous]: -10 °C

Maximum medium temperature [continuous]: 80 °C

Application

- Recommended in: Food & Beverages, Food primary processes [contact with food]



Nominal inner diameter	Material code hose/sleeve	Hose/sleeve material	Maximum control pressure bar	Maximum pressure difference at 20 °C bar	Article
DN65	NBR-LW	NR (natural rubber) white	8	6	12392117
DN15	EPDM	EPDM	8	6	12306144
DN20	EPDM	EPDM	8	6	12381073
DN25	EPDM	EPDM	8	6	12369865
DN50	EPDM	EPDM	8	6	12306145
DN65	EPDM	EPDM	8	6	12378740
DN65	NR-LX	NR (natural rubber) white	8	6	12225684

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.