AKO Pinch valve Series: VMC-T Type: 210T Pneumatic operated Tri-clamp DIN 32676



Characteristics

Series: VMC-T
Type: 210T
Norm: EN (DIN)
Housing material: Stainless steel
Material quality: 1.4408
Connection: Tri-clamp
Standard connection: DIN 32676
Operation: Pneumatic operated

Minimum medium temperature (continuous): -10 °C
Maximum medium temperature (continuous): 80 °C

Application

- Recommended in: Food & Beverages, Food primary processes (contact with food)

Nominal inner diameter	Material code hose/ sleeve	Hose/sleeve material	Maximum control pressure bar	Maximum pressure difference at 20 °C bar	Article
DN25	NBR-LW	NR (natural rubber) white	8	6	12360341
DN50	NBR-LW	NR (natural rubber) white	8	6	12377368

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR3070088193848305_EN_20.04.2024

ERIKS BV | Tel: +31 88 855 80 04 | E-mail: appendages@eriks.nl