

WALVOIL Monobloc valve QM25

Characteristics

Number of sections: 8 Operation: Manual Pressure feed-through: No

Model	Max. operating pressure bar	Max. oilflow I/min	Max. pressure on T bar	Connections	Article
Conventional	300	40	25	A,B,P,T,T2: 3/8"BSP,T2: 1/2" BSP	12525665
Conventional	300	40	25	A,B,P,T,T2: 3/8"BSP,T2: 1/2" BSP	12525666
Conventional	300	40	25	A,B,P,T,T2: 3/8"BSP,T2: 1/2" BSP	12525667
Conventional	300	40	25	A,B,P,T,T2: 3/8"BSP,T2: 1/2" BSP	12525668
Conventional	300	40	25	A,B,P,T,T2: 3/8"BSP,T2: 1/2" BSP	12525669
Conventional	320	40	25	A,B,P,T,T2: 3/8"BSP,T2: 1/2" BSP	12525664
Conventional	350	40	25	A,B,P,T,T2: 3/8"BSP,T2: 1/2" BSP	12525662
Conventional	350	40	25	A,B,P,T,T2: 3/8"BSP,T2: 1/2" BSP	12525663

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

PR3070088193855673_EN_13.05.2024