



WALVOIL 2SM-A group 2, flange: EUR (96x72 mm), tapered shaft 10: 1:8 M12, N connections: flange

Characteristics

Direction of rotation: Clockwise and counterclockwise



Mounting flange	Drive shaft	Displacement cm ³ /r	Max. operating pressure bar	Inlet port	Outlet port	Position oil ports	Code	Article
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	4	210	European flanged ports 30/12/M6	European flanged ports 30/12/M6	Side	2SM-A-040-R-EUR-H-N-10-0-N	13307383
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	4	250	European flanged ports 30/12/M6	European flanged ports 30/12/M6	Side	2SM-A-040-D-EUR-H-N-10-0-N	13307373
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	6	210	European flanged ports 30/12/M6	European flanged ports 30/12/M6	Side	2SM-A-060-R-EUR-H-N-10-0-N	13307384
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	6	250	European flanged ports 30/12/M6	European flanged ports 30/12/M6	Side	2SM-A-060-D-EUR-H-N-10-0-N	13307374
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	11	210	European flanged ports 40/19/M8	European flanged ports 40/19/M8	Side	2SM-A-110-R-EUR-H-N-10-0-N	13307386
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	11	250	European flanged ports 40/19/M8	European flanged ports 30/12/M6	Side	2SM-A-110-D-EUR-H-N-10-0-N	13307376
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	14	210	European flanged ports 40/19/M8	European flanged ports 40/19/M8	Side	2SM-A-140-R-EUR-H-N-10-0-N	13307387
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	14	250	European flanged ports 40/19/M8	European flanged ports 30/12/M6	Side	2SM-A-140-D-EUR-H-N-10-0-N	13307377
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	26	145	European flanged ports 40/19/M8	European flanged ports 40/19/M8	Side	2SM-A-260-R-EUR-H-N-10-0-N	13307391
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	26	170	European flanged ports 40/19/M8	European flanged ports 30/12/M6	Side	2SM-A-260-D-EUR-H-N-10-0-N	13307381
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	8,5	210	European flanged ports 30/12/M6	European flanged ports 30/12/M6	Side	2SM-A-080-R-EUR-H-N-10-0-N	13307385
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	8,5	250	European flanged ports 30/12/M6	European flanged ports 30/12/M6	Side	2SM-A-080-D-EUR-H-N-10-0-N	13307375
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	16,5	195	European flanged ports 40/19/M8	European flanged ports 40/19/M8	Side	2SM-A-160-R-EUR-H-N-10-0-N	13307388
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	16,5	230	European flanged ports 40/19/M8	European flanged ports 30/12/M6	Side	2SM-A-160-D-EUR-H-N-10-0-N	13307378
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 [M12]	19,5	180	European flanged ports 40/19/M8	European flanged ports 40/19/M8	Side	2SM-A-190-R-EUR-H-N-10-0-N	13307389

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Mounting flange	Drive shaft	Displacement cm ³ /r	Max. operating pressure bar	Inlet port	Outlet port	Position oil ports	Code	Article
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 (M12)	19,5	210	European flanged ports 40/19/M8	European flanged ports 30/12/M6	Side	2SM-A-190-D- EUR-H-N-10-0-N	13307379
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 (M12)	22,5	160	European flanged ports 40/19/M8	European flanged ports 40/19/M8	Side	2SM-A-220-R- EUR-H-N-10-0-N	13307390
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 (M12)	22,5	190	European flanged ports 40/19/M8	European flanged ports 30/12/M6	Side	2SM-A-220-D- EUR-H-N-10-0-N	13307380
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 (M12)	31,5	110	European flanged ports 40/19/M8	European flanged ports 40/19/M8	Side	2SM-A-310-R- EUR-H-N-10-0-N	13307392
European GR.2 (96x71 mm) ø 36,5 mm	European tapered 1:8 (M12)	31,5	130	European flanged ports 40/19/M8	European flanged ports 30/12/M6	Side	2SM-A-310-D- EUR-H-N-10-0-N	13307382

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.