

WALVOIL 3GM-G group 3, flange: EUR (128x98 mm), tapered shaft 10: 1:8 M14, N connections: flange

Characteristics

Direction of rotation: Clockwise and counterclockwise



Mounting flange	Drive shaft	Displacement cm ³ /r	Max. operating pressure bar	Inlet port	Outlet port	Position oil ports	Code	Article
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	19,3	210	European flanged ports 51/27/M10	European flanged ports 51/27/M10	Side	3GM-G-190-R-EUR-H-N-10-0-N	13307403
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	19,3	250	European flanged ports 51/27/M10	European flanged ports 40/19/M8	Side	3GM-G-190-D-EUR-H-N-10-0-N	13307393
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	23,0	205	European flanged ports 51/27/M10	European flanged ports 51/27/M10	Side	3GM-G-230-R-EUR-H-N-10-0-N	13307404
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	23,0	240	European flanged ports 51/27/M10	European flanged ports 40/19/M8	Side	3GM-G-230-D-EUR-H-N-10-0-N	13307394
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	30,2	190	European flanged ports 51/27/M10	European flanged ports 51/27/M10	Side	3GM-G-300-R-EUR-H-N-10-0-N	13307405
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	30,2	220	European flanged ports 51/27/M10	European flanged ports 40/19/M8	Side	3GM-G-300-D-EUR-H-N-10-0-N	13307395
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	33,8	190	European flanged ports 51/27/M10	European flanged ports 51/27/M10	Side	3GM-G-340-R-EUR-H-N-10-0-N	13307406
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	33,8	220	European flanged ports 51/27/M10	European flanged ports 40/19/M8	Side	3GM-G-340-D-EUR-H-N-10-0-N	13307396
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	37,5	180	European flanged ports 51/27/M10	European flanged ports 51/27/M10	Side	3GM-G-370-R-EUR-H-N-10-0-N	13307407
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	37,5	210	European flanged ports 51/27/M10	European flanged ports 40/19/M8	Side	3GM-G-370-D-EUR-H-N-10-0-N	13307397
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	44,6	170	European flanged ports 51/27/M10	European flanged ports 51/27/M10	Side	3GM-G-440-R-EUR-H-N-10-0-N	13307408
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	44,6	200	European flanged ports 51/27/M10	European flanged ports 40/19/M8	Side	3GM-G-440-D-EUR-H-N-10-0-N	13307398
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	53,0	170	European flanged ports 51/27/M10	European flanged ports 51/27/M10	Side	3GM-G-530-R-EUR-H-N-10-0-N	13307409
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	53,0	200	European flanged ports 51/27/M10	European flanged ports 40/19/M8	Side	3GM-G-530-D-EUR-H-N-10-0-N	13307399
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 [M14]	62,7	150	European flanged ports 51/27/M10	European flanged ports 51/27/M10	Side	3GM-G-620-R-EUR-H-N-10-0-N	13307410

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Mounting flange	Drive shaft	Displacement cm ³ /r	Max. operating pressure bar	Inlet port	Outlet port	Position oil ports	Code	Article
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 (M14)	62,7	180	European flanged ports 51/27/M10	European flanged ports 40/19/M8	Side	3GM-G-620-D- EUR-H-N-10-0-N	13307400
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 (M14)	70,5	145	European flanged ports 51/27/M10	European flanged ports 51/27/M10	Side	3GM-G-700-R- EUR-H-N-10-0-N	13307411
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 (M14)	70,5	180	European flanged ports 51/27/M10	European flanged ports 40/19/M8	Side	3GM-G-700-D- EUR-H-N-10-0-N	13307401
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 (M14)	77,2	145	European flanged ports 51/27/M10	European flanged ports 51/27/M10	Side	3GM-G-770-R- EUR-H-N-10-0-N	13307412
European GR.3 (128x98 mm) ø 50,8 mm	European tapered 1:8 (M14)	77,2	170	European flanged ports 51/27/M10	European flanged ports 40/19/M8	Side	3GM-G-770-D- EUR-H-N-10-0-N	13307402

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.