



WALVOIL 2SP-A group 2, flange: B50CX (60x60 mm), tapered shaft 11: 1:5 M12, T connections: flange D

Characteristics

Mounting flange: German (60x60 mm) ø 50 mm

Drive shaft: German tapered 1:5 (M12)

Execution (single/tandem): Single

Type: External Gear Pump

Position oil ports: Side

Seal material: NBR

Shaft seal type: Standard

Displacement cm ³ /r	Direction of rotation	Max. operating pressure bar	Inlet port	Outlet port	Code	Article
4	Clockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-040-D-B50CX-B- N-11-O-T	13339541
4	Counterclockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-040-S-B50CX-B- N-11-O-T	13339551
6	Clockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-060-D-B50CX-B- N-11-O-T	13339542
6	Counterclockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-060-S-B50CX-B- N-11-O-T	13339552
11	Clockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-110-D-B50CX-B- N-11-O-T	13339544
11	Counterclockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-110-S-B50CX-B- N-11-O-T	13339554
14	Clockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-140-D-B50CX-B- N-11-O-T	13339545
14	Counterclockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-140-S-B50CX-B- N-11-O-T	13339555
26	Clockwise	170	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-260-D-B50CX-B- N-11-O-T	13339549
26	Counterclockwise	170	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-260-S-B50CX-B- N-11-O-T	13339559
8,5	Clockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-080-D-B50CX-B- N-11-O-T	13339543
8,5	Counterclockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-080-S-B50CX-B- N-11-O-T	13339553
16,5	Clockwise	230	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-160-D-B50CX-B- N-11-O-T	13339546
16,5	Counterclockwise	230	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-160-S-B50CX-B- N-11-O-T	13339556
19,5	Clockwise	210	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-190-D-B50CX-B- N-11-O-T	13339547
19,5	Counterclockwise	210	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-190-S-B50CX-B- N-11-O-T	13339557
22,5	Clockwise	190	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-220-D-B50CX-B- N-11-O-T	13339548
22,5	Counterclockwise	190	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-220-S-B50CX-B- N-11-O-T	13339558
31,5	Clockwise	130	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-310-D-B50CX-B- N-11-O-T	13339550
31,5	Counterclockwise	130	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-310-S-B50CX-B- N-11-O-T	13339560

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.