



WALVOIL 2SP-A group 2, flange: B50CY (60x60 mm), tapered shaft 11: 1:5 M12, N connections: flange

Characteristics

Mounting flange: German (60x60 mm) ø 50 mm

Drive shaft: German tapered 1:5 [M12]

Execution (single/tandem): Single

Type: External Gear Pump

Position oil ports: Side

Seal material: NBR

Shaft seal type: Standard

Displacement cm ³ /r	Direction of rotation	Max. operating pressure bar	Inlet port	Outlet port	Code	Article
4	Clockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-040-D-B50CY-B- N-11-0-N	13339561
4	Counterclockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-040-S-B50CY-B- N-11-0-N	13339571
6	Clockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-060-D-B50CY-B- N-11-0-N	13339562
6	Counterclockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-060-S-B50CY-B- N-11-0-N	13339572
11	Clockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-110-D-B50CY-B- N-11-0-N	13339564
11	Counterclockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-110-S-B50CY-B- N-11-0-N	13339574
14	Clockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-140-D-B50CY-B- N-11-0-N	13339565
14	Counterclockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-140-S-B50CY-B- N-11-0-N	13339575
26	Clockwise	170	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-260-D-B50CY-B- N-11-0-N	13339569
26	Counterclockwise	170	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-260-S-B50CY-B- N-11-0-N	13339579
8,5	Clockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-080-D-B50CY-B- N-11-0-N	13339563
8,5	Counterclockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-080-S-B50CY-B- N-11-0-N	13339573
16,5	Clockwise	230	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-160-D-B50CY-B- N-11-0-N	13339566
16,5	Counterclockwise	230	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-160-S-B50CY-B- N-11-0-N	13339576
19,5	Clockwise	210	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-190-D-B50CY-B- N-11-0-N	13339567
19,5	Counterclockwise	210	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-190-S-B50CY-B- N-11-0-N	13339577
22,5	Clockwise	190	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-220-D-B50CY-B- N-11-0-N	13339568
22,5	Counterclockwise	190	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-220-S-B50CY-B- N-11-0-N	13339578
31,5	Clockwise	130	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-310-D-B50CY-B- N-11-0-N	13339570
31,5	Counterclockwise	130	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-310-S-B50CY-B- N-11-0-N	13339580

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.