



WALVOIL 2SP-A group 2, flange: B80C (100x72 mm), cylindrical shaft 12: 15 mm, T connections: flange D

Characteristics

Mounting flange: German (100x72 mm) ø 80 mm

Drive shaft: Cylindrical 15 mm

Execution (single/tandem): Single

Type: External Gear Pump

Position oil ports: Side

Seal material: NBR

Shaft seal type: Standard

Displacement cm ³ /r	Direction of rotation	Max. operating pressure bar	Inlet port	Outlet port	Code	Article
4	Clockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-040-D-B80C-B- N-12-0-T	13339501
4	Counterclockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-040-S-B80C-B- N-12-0-T	13339511
6	Clockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-060-D-B80C-B- N-12-0-T	13339502
6	Counterclockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-060-S-B80C-B- N-12-0-T	13339512
11	Clockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-110-D-B80C-B- N-12-0-T	13339504
11	Counterclockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-110-S-B80C-B- N-12-0-T	13339514
14	Clockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-140-D-B80C-B- N-12-0-T	13339505
14	Counterclockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-140-S-B80C-B- N-12-0-T	13339515
26	Clockwise	170	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-260-D-B80C-B- N-12-0-T	13339509
26	Counterclockwise	170	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-260-S-B80C-B- N-12-0-T	13339519
8,5	Clockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-080-D-B80C-B- N-12-0-T	13339503
8,5	Counterclockwise	250	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-080-S-B80C-B- N-12-0-T	13339513
16,5	Clockwise	230	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-160-D-B80C-B- N-12-0-T	13339506
16,5	Counterclockwise	230	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-160-S-B80C-B- N-12-0-T	13339516
19,5	Clockwise	210	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-190-D-B80C-B- N-12-0-T	13339507
19,5	Counterclockwise	210	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-190-S-B80C-B- N-12-0-T	13339517
22,5	Clockwise	190	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-220-D-B80C-B- N-12-0-T	13339508
22,5	Counterclockwise	190	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-220-S-B80C-B- N-12-0-T	13339518
31,5	Clockwise	130	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-310-D-B80C-B- N-12-0-T	13339510
31,5	Counterclockwise	130	German flanged 40/20/M6	ports German flanged 35/15/M6	2SP-A-310-S-B80C-B- N-12-0-T	13339520

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.